



Liqui-Cel™
Membrane Contactors

LENNTECH
WATER TREATMENT SOLUTIONS

3M™ Liqui-Cel™ EXF-4×28 Series Membrane Contactor


Typical Properties

Membrane Characteristics		
Cartridge Configuration	Extra-Flow with Center Baffle	
Liquid Flow Guidelines	0.9 – 6.8 m ³ /hr (4 – 30 gpm)	
Membrane Type	X50	X40
	Recommended for CO ₂ removal from water	Recommended for all other gas transfer applications
Membrane/Potting Material	Polypropylene / Polyethylene	
Priming Volume (approximate)		
Shellside X40 or X50	4.2 L (1.1 gal) PP housing, 3.0 L (0.8 gal) SS housing	
Lumenside X50	1.3 L (0.4 gal) PP housing, 1.0 L (0.3 gal) SS housing	
Lumenside X40	1.1 L (0.3 gal) PP housing, 0.9 L (0.2 gal) SS housing	

Pressure Guidelines*			
	PP X50 or X40	316L SS X50	316L SS X40
Maximum Shellside <u>LIQUID</u> Working Temperature/ Pressure	5-30°C, 7.2 barg (41-86°F, 105 psig)	5-50°C, 7.2 barg (41-122°F, 105 psig)	5-50°C, 9.3 barg (41-122°F, 135 psig)
	40°C, 5.2 barg (104°F, 75 psig)	70°C, 2.1 barg (158°F, 30 psig)	70°C, 2.1 barg (158°F, 30 psig)
If no vacuum is used, 1 barg (15 psig) can be added to pressures above.			
Maximum Applied Gas Pressure	4.1 barg at 25°C (60 psig at 77°F)	6.2 barg at 25°C (90 psig at 77°F)	
Maximum applied gas pressure is for integrity testing at ambient temperatures. Normal operating pressures are typically lower.			
* See Operating Guide for complete temp/pressure limits for housings and membrane.			
Note: Liquid pressure should always exceed gas pressure.			

Housing Options and Characteristics		
Material	Polypropylene	316L SS Surface Finish ≤ 0.8µm SI (32 RA)
Flange Connections		
Shellside (Liquid Inlet/Outlet)	1 inch Sanitary ¾ inch NPT Female 1 inch George Fisher Rc ¾ per JIS B0203	1 inch Sanitary
Lumenside (gas/vacuum)	1 inch 90° Sanitary ¾ inch 90° NPT Female Rc ¾ per JIS B0203	1 inch Sanitary

Seal Options	
Material	Applications
Viton	General Purpose
K - UPW	Ultra Pure Water
K - EXT	Chemical Extraction
Buna-N	Beverage



All dimensions are nominal values for the Polypropylene housing. See full housing drawing on 3M.com/Liqui-Cel for additional details.




3M™ Liqui-Cel™ EXF-4x28 Series Membrane Contactor

Typical Properties

Weight (approximate)	PP	316L SS
Dry (cartridge and housing)	4 kg (9 lbs)	7 kg (15 lbs)
Water-filled (shellside)	7 kg (15 lbs)	10 kg (21 lbs)
Cartridge only – dry	X50: 1 kg (2 lbs), X40: 1 kg (3 lbs)	

Regulatory

Complies with the limits as set by RoHS Directive 2011/65/EU Annex II; recasting 2002/95/EC.
Constructed of FDA CFR title 21 compliant materials for wetted parts only at ambient temperatures.



Curves represent nominal values. Characteristics may change under different operating conditions.
Test condition O₂ Removal with X40 membrane 20°C (68°F): N₂-vacuum combo mode, vacuum: 50 mm Hg N₂ sweep flow 1.4 L/min (0.05 scfm). Vacuum mode: 50 mm Hg.
Test condition CO₂ Removal with X50 membrane 20°C (68°F): Air-vacuum combo mode, air sweep: 4 G/L, vacuum: 150 mm Hg.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M and Liqui-Cel are trademarks of 3M Company. All other trademarks are the property of their respective owners. © 2017 3M Company. All rights reserved.



ISO 9001



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

LC-1041
Rev. 01/2017