

Product Information Sheet

ADVANTAGES

- High strength powder formulation specifically designed to remove metal oxides from polyamide thin film composite membrane surfaces and water softener resins
- Produces an effervescent bubbling effect that improves cleaning efficacy
- Effective in dispersing some biofilms that may have formed a matrix with the metal oxides
- Assists in removal of carbonate and sulfate scales
- Compatible with all Thin Film Composite R.O. membranes from all major membrane suppliers
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	White to tan powder
Odor	Characteristic
Solubility in water	Complete
pH (1% Solution)	4 - 5

PACKAGING

50 lb. pails and 400 lb. non-returnable plastic drums

AWC® C-225

Iron Removing Membrane and
Softener Resin Cleaning Compound

SAFETY & HANDLING

Store in cool, dry and well ventilated area. Keep containers closed. Wash contaminated clothes before re-use. Wash thoroughly after handling. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

The water used to prepare the solution should be potable and free of residual chlorine or other oxidizing agents. The cleaning solution is prepared by adding 12–13 lbs of AWC C-225 for every 100 gallons of water (1.5 wt% Solution). The cleaning solution is then circulated throughout the system.

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

