

CA AX polyester felt filtering medium and granular activated carbon - 25 micron throw-away cartridge



APPLICATIONS

Pre-Filtration and elimination of: unpleasant odours and flavours from water caused by chlorine and other organic substances; removal of pesticides, insecticides, chlorinate solvents.

Domestic use: filtration and anti-chlorine treatment in point-of-entry appliances and in point-of-use appliances: washing machines, showers and drinking water units.

Technical use: anti-chlorine treatment in alimentary, chemical and pharmaceutical industry, pre-treatment for the protection of reverse osmosis units.

Average life-span: 3 months.

Maintenance: none.

WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non toxic materials, suitable for drinking water.


Filtering medium: polyester felt.

End caps and grid: polypropylene.

O-rings: ETP.

Treating material: granular activated carbon of coconut shell.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	CA 5 AX 25 mcr	5"	125	70	25	300
Junior	CA 7 AX 25 mcr	7"	173	70	25	450
Senior	CA 10 AX 25 mcr	10"	250	70	25	600
Master	CA 20 AX 25 mcr	20"	505	70	25	1200



VARIANTS available on minimum quantity

AG Cartridges with granular activated carbon silver treated for bacteriostatic action.

KDF Cartridges with KDF® for reduction of heavy-metals.

LA AX container with granular activated carbon throw-away cartridge



APPLICATIONS

Elimination of: unpleasant odours and flavours from water caused by chlorine and other organic substances; removal of pesticides, insecticides, chlorinate solvents.

Domestic use: anti-chlorine treatment in point-of-entry appliances and in point-of-use appliances: washing machines, showers and drinking water units.

Technical use: anti-chlorine treatment in alimentary, chemical and pharmaceutical industry, pre-treatment for the protection of reverse osmosis units.

Average life-span: 3 months.

Maintenance: none.

Remark - Use a pre-filter to protect the cartridge.

WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Container: polystyrene.


End cap and grid: polystyrene.

O-rings: ETP.

Containing sponge: polyurethane.

Treating material: granular activated carbon of coconut shell.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	LA 5 AX-TS	5"	127	72	25	400
Junior	LA 7 AX-TS	7"	183	72	25	400
Senior	LA 10 AX-TS	10"	252	72	25	400
Master	LA 20 AX-TS	20"	510	72	25	400



VARIANTS available on minimum quantity

Cartridges with different heights.

AG Cartridges with granular activated carbon silver treated for bacteriostatic action.

KDF Cartridges with KDF® for reduction of heavy-metals.

Cartridges with opaque container.

LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289