

RA AX stainless steel filtering net - 70 micron washable cartridge



APPLICATIONS

Filtration of: sand, scale, rust.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.

Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only RA-A stainless steel AISI 316 type).

Average life-span: RA-A about 5 years, RA-C about 3 years.

Maintenance: wash every 3 months.

WORKING CONDITIONS

Max working temperature _____ 45°C

CARATTERISTICHE

Non-toxic materials, suitable for drinking water.

Filtering medium: stainless steel net AISI 316 or AISI 304.

Inner armouring: stainless steel AISI 316 or AISI 304.


Inner core: polypropylene.

End caps: polypropylene.

O-rings: ETP.

suitable housing	cartridge RA-A AISI 316	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RA 5-A AX 70 mcr	5"	125	70	25	800
Junior	RA 7-A AX 70 mcr	7"	173	70	25	1100
Senior	RA 10-A AX 70 mcr	10"	250	70	25	1600
Master	RA 20-A AX 70 mcr	20"	505	70	25	3000

suitable housing	cartridge RA-C AISI 304	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RA 5-C AX 70 mcr	5"	125	70	25	800
Junior	RA 7-C AX 70 mcr	7"	173	70	25	1100
Senior	RA 10-C AX 70 mcr	10"	250	70	25	1600
Master	RA 20-C AX 70 mcr	20"	505	70	25	3000



VARIANTS available on minimum quantity

Cartridges with different filtration rates.

SA AX pleated stainless steel filtering net - 50 micron washable cartridge



APPLICATIONS

Filtration of: sand, scale, rust.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.

Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only SA-A stainless steel AISI 316 type).

Average life-span: SA-A about 5 years, SA-C about 3 years

Maintenance: wash every 3 months.

WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Filtering medium: stainless steel net AISI 316 or AISI 304.


Inner core: polypropylene.

End caps: polypropylene.

O-rings: ETP.

suitable housing	cartridge SA-A AISI 316	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	SA 5-A AX 50 mcr	5"	125	70	25	1100
Junior	SA 7-A AX 50 mcr	7"	173	70	25	1500
Senior	SA 10-A AX 50 mcr	10"	250	70	25	2200
Master	SA 20-A AX 50 mcr	20"	505	70	25	3800

suitable housing	cartridge SA-C AISI 304	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	SA 5-C AX 50 mcr	5"	125	70	25	1100
Junior	SA 7-C AX 50 mcr	7"	173	70	25	1500
Senior	SA 10-C AX 50 mcr	10"	250	70	25	2200
Master	SA 20-C AX 50 mcr	20"	505	70	25	3800



VARIANTS available on minimum quantity

Cartridges with different filtration rates.