

# RA BX stainless steel filtering net - 70 micron washable cartridge



## APPLICATIONS

**Filtration of:** sand, scale, rust.

**Domestic use:** filtration of drinking water, protection of taps, boilers, washing machines and other installations.

**Technical use:** pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only RA-A stainless steel AISI 316 type).

**Average life-span:** RA-A about 5 years, RA-C about 3 years.

**Maintenance:** wash every 3 months.

## WORKING CONDITIONS

Max working temperature \_\_\_\_\_ 45°C

## CARATTERISTICHE

Non-toxic materials, suitable for drinking water.

**Filtering medium:** stainless steel net AISI 316 or AISI 304.

**Inner armouring:** stainless steel AISI 316 or AISI 304.

**Inner core:** polypropylene.


**End caps:** polypropylene.

**O-rings:** ETP.

| suitable housing | cartridge RA-A<br>AISI 316 | cartridge height | mm  |    |    | recommended flow rate l/h |
|------------------|----------------------------|------------------|-----|----|----|---------------------------|
|                  |                            |                  | A   | B  | C  |                           |
| Medium           | RA 5-A BX 70 mcr           | 5"               | 125 | 70 | 32 | 800                       |
| Junior           | RA 7-A BX 70 mcr           | 7"               | 173 | 70 | 32 | 1100                      |
| Senior           | RA 10-A BX 70 mcr          | 10"              | 250 | 70 | 32 | 1600                      |
| Master           | RA 20-A BX 70 mcr          | 20"              | 505 | 70 | 32 | 3000                      |

| suitable housing | cartridge RA-C<br>AISI 304 | cartridge height | mm  |    |    | recommended flow rate l/h |
|------------------|----------------------------|------------------|-----|----|----|---------------------------|
|                  |                            |                  | A   | B  | C  |                           |
| Medium           | RA 5-C BX 70 mcr           | 5"               | 125 | 70 | 32 | 800                       |
| Junior           | RA 7-C BX 70 mcr           | 7"               | 173 | 70 | 32 | 1100                      |
| Senior           | RA 10-C BX 70 mcr          | 10"              | 250 | 70 | 32 | 1600                      |
| Master           | RA 20-C BX 70 mcr          | 20"              | 505 | 70 | 32 | 3000                      |



**VARIANTS** available on minimum quantity

Cartridges with different filtration rates.

# SA BX pleated stainless steel filtering net - 50 micron washable cartridge



## APPLICATIONS

**Filtration of:** sand, scale, rust.

**Domestic use:** filtration of drinking water, protection of taps, boilers, washing machines and other installations.

**Technical use:** pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only SA-A stainless steel AISI 316 type).

**Average life-span:** SA-A about 5 years, SA-C about 3 years

**Maintenance:** wash every 3 months.

## WORKING CONDITIONS

Max working temperature \_\_\_\_\_ 45°C

## SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

**Filtering medium:** stainless steel net AISI 316 or AISI 304.

**Inner core:** polypropylene.


**End caps:** polypropylene.

**O-rings:** ETP.

| suitable housing | cartridge SA-A<br>AISI 316 | cartridge height | mm  |    |    | recommended flow rate l/h |
|------------------|----------------------------|------------------|-----|----|----|---------------------------|
|                  |                            |                  | A   | B  | C  |                           |
| Medium           | SA 5-A BX 50 mcr           | 5"               | 125 | 70 | 32 | 1100                      |
| Junior           | SA 7-A BX 50 mcr           | 7"               | 173 | 70 | 32 | 1500                      |
| Senior           | SA 10-A BX 50 mcr          | 10"              | 250 | 70 | 32 | 2200                      |
| Master           | SA 20-A BX 50 mcr          | 20"              | 505 | 70 | 32 | 3800                      |

| suitable housing | cartridge SA-C<br>AISI 304 | cartridge height | mm  |    |    | recommended flow rate l/h |
|------------------|----------------------------|------------------|-----|----|----|---------------------------|
|                  |                            |                  | A   | B  | C  |                           |
| Medium           | SA 5-C BX 50 mcr           | 5"               | 125 | 70 | 32 | 1100                      |
| Junior           | SA 7-C BX 50 mcr           | 7"               | 173 | 70 | 32 | 1500                      |
| Senior           | SA 10-C BX 50 mcr          | 10"              | 250 | 70 | 32 | 2200                      |
| Master           | SA 20-C BX 50 mcr          | 20"              | 505 | 70 | 32 | 3800                      |



**VARIANTS** available on minimum quantity

Cartridges with different filtration rates.