

RL AX polyester filtering net - 50 micron washable cartridge



APPLICATIONS

Filtration of: sand, scale, rust.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.

Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations.

Average life-span: about 24 months.

Maintenance: wash every 3 months.

WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Filtrating medium: polyester net.


Armouring: polypropylene.

End caps: polypropylene.

O-rings: ETP.



suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RL 5 AX 50 mcr	5"	125	70	25	800
Junior	RL 7 AX 50 mcr	7"	173	70	25	1100
Senior	RL 10 AX 50 mcr	10"	250	70	25	1600
Master	RL 20 AX 50 mcr	20"	505	70	25	3000



VARIANTS available on minimum quantity

Cartridges with different filtration rates.

RS AX pleated polypropylene filtering net - 50 micron washable cartridge



APPLICATIONS

Filtration of: sand, scale, rust.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.

Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations.

Average life-span: about 24 months.

Maintenance: wash every 3 months.

WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Filtrating medium: polypropylene net.


Inner core: polypropylene.

End caps: polypropylene.

O-ring: ETP.



suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RS 5 AX 50 mcr	5"	125	70	25	1100
Junior	RS 7 AX 50 mcr	7"	173	70	25	1500
Senior	RS 10 AX 50 mcr	10"	250	70	25	2200
Master	RS 20 AX 50 mcr	20"	505	70	25	3800



VARIANTS available on minimum quantity

Cartridges with different filtration rates.