

housings Duplex Plus 3P AX

for quick-fit cartridges with double O-ring



APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The exclusive DUPLEX housings allow faster and safer installations of serial filtration units.

Domestic use: filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

WORKING CONDITIONS

Max working pressure _____ 8 BAR

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head and ring nut: reinforced polypropylene.

Transparent bowl: SAN.

O-ring: ETP.

Breather-valve: body polypropylene, O-ring ETP.

IN/OUT threads: CW 614 N brass inserts.




Medium

Junior

Master

Senior

Cartridge height	housings with transparent bowl AS IN/OUT female threads with FO brass inserts	IN/OUT threads	mm	
			A	B
5"	Medium Duplex Plus 3P AFO AX AS	3/4"	191	275
5"	Medium Duplex Plus 3P BFO AX AS	1"	191	275
7"	Junior Duplex Plus 3P AFO AX AS	3/4"	241	275
7"	Junior Duplex Plus 3P BFO AX AS	1"	241	275
10"	Senior Duplex Plus 3P AFO AX AS	3/4"	315	275
10"	Senior Duplex Plus 3P BFO AX AS	1"	315	275
20"	Master Duplex Plus 3P AFO AX AS	3/4"	571	275
20"	Master Duplex Plus 3P BFO AX AS	1"	571	275



VARIANTS available on minimum quantity

FP female plastic IN/OUT threads, BSP type 3/4".

AB housings with opaque bowl, impermeable to the light.



-U- spanner



-D- wall bracket



wall bracket screws



3/4" and 1", brass nipples with O-ring

