

A Cost-Efficient Alternative to Phosphonates

Description

Bellasol® S16 offers a unique, cost effective treatment for addressing mixed scale in oilfield brines. This product works in operations at over 180°C, where phosphonates tend to fail. Bellasol® S16 is an aqueous solution of sodium salt of maleic acid.

Application

Formulation with Bellasol® S16 provides:

- Cost efficiency
- Good mixed sulfate/carbonate scales
- Dispersant properties
- Thermodynamic stability

Benefits

Bellasol® S16 antiscalant has been developed as a direct alternative to phosphonates for use in calcium carbonate scales. This product should be used for continuous injection.

Usage

Typical Dosage 15 to 30 ppm

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Drum 507 lb
 230 kg

*Consult your sales representative for availability.

Physical Properties

Appearance Amber Liquid

Odor Slight

Active content 20% w/w

Specific gravity 1.11-1.16 at 20/20°C


pH of undiluted product 8-9 at 20°C

Viscosity <10mm²/s at 25°C

Boiling range (760 mm Hg) 100 - 102°C (212-216°F)

Solubility Miscible in water

Further details are available in the safety data sheet



LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. ® Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.