

Filter Cartridge Housings

BECO INTEGRA CART, KL0 series

1 A 7.2.4 · DW
06/2011

BECO INTEGRA CART KL0 cartridge housings are manufactured of AISI 316L stainless steel and designed for pressurized air or steam filtration.

Special Features

- ▶ The use of material AISI 316L is corrosion resistant, even after long use
- ▶ High safety by use of the Code-7-adapter (double bayonet catch)
- ▶ The optimized housing design allows thorough and fast cleaning
- ▶ Suitable for filtration of gases and particle filtration of steam
- ▶ Suitable for hot water or steam sterilization

Application

All BECO INTEGRA CART KL0 cartridge housings are suitable for the filtration of media within fluid group 2 according to the Pressure Equipment Directive DGRL 97/23/EC. Different stack heights of 10" to 30" allow perfect adaptation of housing size to the product to be filtered. Thanks to an optimized filtrate area design and a special surface finish this housing can be perfectly cleaned and sterilized.

BECO INTEGRA CART cartridge housings accept BECO filter cartridges with code 7 adapter.


Technical Data

Max. permissible operating pressure:	+10 bar
Max. permissible operating temperature:	+140 °C
Housing material:	Stainless steel 1.4404
product contacting:	EPDM
Sealing:	
Housing is suitable for:	Media of fluid group 2 according to DGRL (PED) 97/23/EC
Housings connections:	See table (N1/N2)
Housing closure:	Tri-Clamp
Vent N3:	Sanitary valve G ½"
Drain N4:	Sanitary valve G ½"
Fittings:	Vent and drain units are included in the scope of supply
HS Customs Tariff:	8421 29 90



KL0-housing with G ½" connections

Item no.	Quantity of cartridges	Height of cartridges	Dimensions [mm]				Connections	Weight [kg]	Volume [l]	Permissible pressure [bar]	Permissible temperature [°C]
			A	B	C	D					
KL011040	1	10"	761	158	200	40	DN 40 SS	6.5	3.8	-1/+10	-10/+140
KL012040	1	20"	1011	158	200	40	DN 40 SS	7.8	5.7	-1/+10	-10/+140
KL013040	1	30"	1261	158	200	40	DN 40 SS	9.0	7.6	-1/+10	-10/+140
KL013065	1	30"	1261	158	222	65	DN 65 SS	9.0	7.6	-1/+10	-10/+140
KL0110GA	1	10"	761	158	180	16	G ½" outside	6.5	3.8	-1/+10	-10/+140
KL0130GA	1	30"	1261	158	286	38	G 2 ½" outside	9.0	7.6	-1/+10	-10/+140



All information is given to the best of our knowledge. However, the validity of the information cannot be guaranteed for every application, working practice and operating condition. Misuse of the product will result in all warranties being voided. Reproduction, even in part, is permitted only with reference to the source. Subject to change in the interest of technical progress.

LENNTECH

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89