

# RE8040-FLR

**LENNTECH**  
WATER TREATMENT SOLUTIONS

**CSM**<sup>®</sup>

Fouling resistant RO element with low pressure for brackish water and wastewater reuse

- Fouling resistant
- Low Energy Consumption
- High Permeate Flow and High Rejection



Industrial



Water Reuse

## SPECIFICATIONS

### General Features

|                         |                                            |
|-------------------------|--------------------------------------------|
| Permeate Flow Rate      | 10,000 GPD (37.9 m <sup>3</sup> /day)      |
| Nominal Salt Rejection  | 99.6% (Minimum 99.5%)                      |
| Effective Membrane Area | 400 ft <sup>2</sup> (37.2 m <sup>2</sup> ) |
| Membrane Type           | Thin-Film Composite                        |
| Membrane Material       | Polyamide (PA)                             |
| Element Configuration   | Spiral-Wound, FRP Wrapping                 |

**Test Conditions:** 1,500 mg/L NaCl solution at 150 psig (1.03 MPa) applied pressure; 15% recovery; 77°F(25°C); pH 6.5–7.0; Permeate flow rate for each element may vary but will be no more than -5%.

### Dimensions and Weight

| Model Name | A                       | B                    | C                      | Weight | Part Number     |            |
|------------|-------------------------|----------------------|------------------------|--------|-----------------|------------|
|            |                         |                      |                        |        | Inter-Connector | Brine Seal |
| RE8040-FLR | 40.0 inch<br>(1,016 mm) | 7.9 inch<br>(200 mm) | 1.12 inch<br>(28.5 mm) | 15kg   | SWA01049        | SWA01043   |



1. Each membrane element supplied with one interconnector (coupler) and four O-rings.
2. All RE8040 elements fit nominal 8.0 inch (203.2 mm) I.D. pressure vessels.

# RE8040-FLR

# CSM<sup>®</sup>

Fouling resistant RO element with low pressure for brackish water and wastewater reuse

## APPLICATION DATA

### Operating Limits

|                                         |                                  |
|-----------------------------------------|----------------------------------|
| <b>Max. Pressure Drop / Element</b>     | 15 psi (0.10 MPa)                |
| <b>Max. Pressure Drop / 240" Vessel</b> | 60 psi (0.41 MPa)                |
| <b>Max. Operating Pressure</b>          | 600 psi (4.14 MPa)               |
| <b>Max. Feed Flow Rate</b>              | 75 gpm (17.0 m <sup>3</sup> /hr) |
| <b>Min. Concentrate Flow Rate</b>       | 16 gpm (3.6 m <sup>3</sup> /hr)  |
| <b>Max. Operating Temperature</b>       | 113°F (45°C)                     |
| <b>Operating pH Range</b>               | 2.0 – 11.0                       |
| <b>CIP pH Range</b>                     | 1.0 – 13.0                       |
| <b>Max. Turbidity</b>                   | 1.0 NTU                          |
| <b>Max. SDI (15 min)</b>                | 5.0                              |
| <b>Max. Chlorine Concentration</b>      | < 0.1 mg/L                       |

- Elements contained in the boxes must be kept dry at room temperature (7–32°C; 40–95°F) and should not be stored in direct sunlight.
- For WET-TYPE, the preservative solution (1% sodium metabisulfite solution) is added to prohibit the growth of micro-organisms.
- Permeate from the first hour of operation should be discarded.
- Stabilized salt rejection is generally achieved within 1~48 hours of continuous use.
- Keep elements moist at all times after initial wetting.
- Avoid excessive pressure and flow spikes.
- Only use chemicals compatible with the membrane elements and components. Use of such chemicals may void the element limited warranty.
- Permeate pressure must always be equal or less than the feed/concentrate pressure. Damage caused by permeate back pressure voids the element limited warranty.
- The element shell is FRP(Fiber Reinforced Plastic). Be aware of glass fiber strands and use safety equipment.

Certified to  
NSF/ANSI/CAN 61

**LENNTECH**  
WATER TREATMENT SOLUTIONS

info@lenntech.com Tel. +31-152-610-900  
www.lenntech.com Fax. +31-152-616-289