

3M Purification Inc.

Chemical Compatibility Guide—February 2011

For more information contact:

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89



Innovative
Filtration

Quality. Performance. Service.

For more information contact:

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89



Chemical Filtration Compatibility Guide—February 2011

Legend	System			Lenticular		Cartridge Filters ¹						O-rings/Support Rings				
	Zeta Plus™ Encapsulated System: Standard Capsules	Zeta Plus™ Encapsulated System: Alkaline Resistant Capsules—Pre-Use	Zeta Plus™ Encapsulated System: Alkaline Resistant Capsules—Post-Use	Zeta Plus™ Filter	Zeta Plus™ Activated Carbon Filter	Betafine™ D/Betafine™ XL	PolyPro™ XL/Betapure™ NTP	LifeASSURE™ SA/SP/ST Series	LifeASSURE™ BLA Series	LifeASSURE™ PFS Series	LifeASSURE™ PDA Series	Fluorocarbon	PTFE Encapsulated Fluorocarbon	Silicone	EPR	316 Stainless Steel
R = Recommended																
N = Not Recommended																
LR = Limited Recommendation*																
Blank = No data available																
Acetaldehyde	N			R	R	R	R	R	R	R	N	N	R	R	R	R
Acetic Acid (10%)	LR	LR	LR	LR	LR	R	R	N	N	R	R	LR	R	LR	R	R
Acetic Acid, Glacial	N	N	LR	N	N	R	R	N	N	R	R	N	R	LR	LR	R
Acetic Anhydride	N	N	N	N	N	LR	LR	R	R	R		N	R	LR	LR	R
Acetone	N	N	N	LR	LR	R	R	R	R	R	N	N	R	N	R	R
Ammonia	N	N	LR	N	N	R	R	R	R	R		N	R	LR	R	R
Ammonium Hydroxide (Conc.)	N	LR	R	LR	LR	R	R	R	R	R	R	LR	R	R	R	R
Benzaldehyde	N	N	N	LR	LR	LR	LR	N	R	R	R	N	R	N	R	LR
Benzene	N	N	N	N	N	N	N	N	N	N	N	R	R	N	N	LR
Butyl Acetate	N	N	N	R	R	LR	LR	R	R	R	LR	N	R	N	LR	R
Carbon Tetrachloride	N	N	N	LR	LR	N	N	LR	LR	R	N	R	R	N	N	R
Chlorine, Anhydrous Liquid	N	N	N	N	N	N	N	N	N	N	N	R	R	N	LR	LR
Chloroform	N	N	N	LR	LR	LR	LR	LR	LR	LR	N	R	R	N	N	R
Citric Acid	LR	LR	R	LR	LR	R	R	R	R	R	R	R	R	R	R	R
Cyclohexane	N	N	N	LR	LR	LR	LR	LR	LR	LR	LR	R	R	N	LR	R
Cyclohexanone	N	N	N	LR	LR	LR	LR	LR	LR	N	N	N	R	N	LR	R
Diethylamine	N					R	R	R	R	R	R	N	N	LR	LR	R
Ethanol		LR	LR	R	R	R	R	R	R	R	R	N	R	LR	R	R
Ethyl Acetate	N	N	N	R	R	LR	LR	R	R	R	N	N	R	LR	LR	R
Ethylene Glycol	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
Ethylene Oxide	N	N	N	LR	LR	LR	LR	LR	LR	LR	LR	N	R	N	N	R
Formaldehyde—40%	LR	LR	LR	LR	LR	R	R	R	R	R	R	N	R	LR	R	R
Glycerol	R	LR	LR	R	R	R	R	R	R	R	R	R	R	R	R	R
Heptane	N	N	N	N	N	N	N	N	N	N	N	R	R	N	N	R
Hexane	N	N	N	LR	LR	LR	LR	LR	LR	LR	LR	R	R	N	N	R
Hydrobromic Acid—20%	N	N	N	N	N	LR	LR	N	N	LR		R	R	N	R	N
Hydrochloric Acid—20%	N	N	N	N	N	LR	LR	N	N	R	R	R	R	N	R	N
Hydrofluoric Acid—20%	N	N	N	N	N	LR	LR	N	N	R	LR	R	R	N	N	N
Hydrogen Peroxide—30%	N	N	LR	N	N	R	R	N	N	R	R	R	R	LR	N	R
Hydrogen Sulfide (Aqua)	N	N	N	R	R	R	R	N	N	R	LR	N	R	N	R	R
Isopropyl Alcohol	R	R	R	R	R	R	R	LR	LR	R	R	R	R	R	R	R
Maleic Acid		LR	LR	LR	LR	R	R	LR	LR	R		R	R	LR	N	R
Methanol	R	R	R	R	R	R	R	R	R	R	R	N	R	R	R	R
Methyl Chloride	N	N	N	LR	LR	N	N	LR	LR	LR	N	R	R	N	N	R

Chemical Compatibility Guide

February 2011


Legend	System			Lenticular		Cartridge Filters ¹						O-rings/Support Rings				
R = Recommended N = Not Recommended LR = Limited Recommendation* Blank = No data available	Zeta Plus™ Encapsulated System: Standard Capsules	Zeta Plus™ Encapsulated System: Alkaline Resistant Capsules—Pre-Use	Zeta Plus™ Encapsulated System: Alkaline Resistant Capsules—Post-Use	Zeta Plus™ Filter	Zeta Plus™ Activated Carbon Filter	Betafine™ D/Betafine™ XL	PolyPro™ XL/Betapure™ NTP	LifeASSURE™ SA/SP/ST Series	LifeASSURE™ BLA Series	LifeASSURE™ PFS Series	LifeASSURE™ PDA Series	Fluorocarbon	PTFE Encapsulated Fluorocarbon	Silicone	EPR	316 Stainless Steel
Methyl Ethyl Ketone (MEK)	N	N	N	LR	LR	LR	LR	LR	LR	LR	N	N	R	N	R	R
Methylene Chloride	N	N	N	LR	LR	N	N	N	N	R	LR	LR	R	N	N	R
Nitric Acid—20%	N	N	N	N	N	R	R	N	N	R	R	R	R	N	LR	R
Nitric Acid—50%	N	N	N	N	N	LR	LR	N	N	N	N	R	R	N	N	R
Nitric Acid (Conc.)	N	N	N	N	N	N	N	N	N	N	N	R	R	N	N	R
Pentane	N	N	N	LR	LR	LR	LR	LR	LR	LR		R	R	N	N	LR
Perchloroethylene	N	N	N	LR	LR	N	N	LR	LR	R	N	R	R	N	N	R
Phosphoric Acid > 40%	N	N	N	N	N	LR	LR	LR	LR	R	LR	R	R	N	LR	N
Potassium Hydroxide	N	N	N	N	N	R	R	LR	LR	R	N	LR	R	N	R	R
Propylene Glycol				R	R	R	R	R	R	R	R	R	R	R	R	R
Sodium Hydroxide, 20%	N	LR	R	LR	LR	R	R	LR	LR	R	R	LR	R	R	LR	LR
Sodium Hydroxide, 50%	N	LR	R	N	N	R	R	LR	LR	R	R	N	R	R	LR	LR
Sodium Hypochlorite—5%	N	N	LR	N	N	R	R	N	N	R	R	R	R	LR	LR	N
Sulfuric Acid—5%	LR	LR	LR	LR	LR	R	R	N	N	R	R	R	R	LR	R	LR
Sulfuric Acid—10%	N	N	N	N	N	R	R	N	N	R	R	R	R	N	LR	N
Sulfuric Acid—20%	N	N	N	N	N	R	R	N	N	R	R	R	R	N	LR	N
Sulfuric Acid—50%	N	N	N	N	N	R	R	N	N	R	R	R	R	N	LR	N
Sulfuric Acid—80%	N	N	N	N	N	LR	LR	N	N	LR	R	R	R	N	LR	N
Tetrachloroethylene	N	N	N	LR	LR	N	N	LR	LR	R		R	R	N	N	R
Tetrahydrofuran, THF	N	N	N	LR	LR	LR	LR	R	R	R	N	N	R	N	N	R
Toluene	N	N	N	LR	LR	N	N	LR	LR	LR	N	LR	R	N	N	R
Trichloroethane	N	N	N	LR	LR	N	N	LR	LR	LR	LR	R	R	N	N	R
Trichloroethylene	N	N	N	LR	LR	N	N	N	N	R	N	R	R	N	N	R
Xylene	N	N	N	LR	LR	N	N	LR	LR	LR	LR	R	R	N	N	R

* LR: Please verify compatibility with fluid prior to use.

¹ Note: When using a filter cartridge which contains a stainless steel reinforcing ring, consult chemical compatibility of stainless steel.

Compatibility recommendations are given at room or ambient temperature conditions.

This listing is intended as a guide for selecting the appropriate 3M Purification Inc. filter based on compatibility with most common chemicals used in pharmaceutical manufacturing. This information is based on technical publications, laboratory experiments, data from material suppliers and field tests. 3M Purification Inc. recommends that compatibility be established by the customer in their specific application because actual performance may differ as a result of variations in temperature, concentration, exposure time, or other factors. Consideration must also be given in selecting a suitable O-ring material to ensure compatibility.



Important Notice

The information described in this literature is accurate to the best of our knowledge. A variety of factors, however, can affect the performance of the Product(s) in a particular application, some of which are uniquely within your knowledge and control. **INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING THE SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR USE. IN NO EVENT WILL 3M PURIFICATION INC. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION.**

It is your responsibility to determine if additional testing or information is required and if this product is fit for a particular purpose and suitable in your specific application.

3M PURIFICATION INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.



For more information contact:

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

3M is a trademark of 3M Company.
 Betafine, Betapure, PolyPro, LifeASSURE
 and Zeta Plus are trademarks of
 3M Company used under license.
 © 3M 2011. All rights reserved.
 70-0202-2023-5 REV 0111