

Technical data Corode filter unit

CF07..M


6600l/h – Filter housing PP or PVDF material

LENNTECH
WATER TREATMENT Solutions



Corode unit with magnetic drive pump **CPMD-07**.

Q max :6.6m³/h
Q min :1m³/h
Pump head :PP or PVDF
Motor :0.25kW, 400V, 1.29/0.74Amp, 3Ph, 50Hz, IP55
:0.25kW, 230V, 1.92Amp, 1Ph, 50Hz, IP55
Other voltage options and 60Hz available on request.



Filter housing in PP maximum temp 80°C
Filter housing in PVDF maximum temp 100°C
Outside metal SS316
Height filter housing: 10", 20", 30"

Standard units include:

Thermal overload switch
Air release/ drain valve
Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
Hand priming pump
Transport wheels
Precoat tank PP 10"xØ225 (10 liter)
20"xØ225 (20 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF07CM PP	45	35	85	Ø32mm	Ø32mm	Cartridge 7x10"	2.31
CF07PM PP	45	35	85	Ø32mm	Ø32mm	Paper 41xØ215	1.25
CF07C20M PP	45	35	115	Ø32mm	Ø32mm	Cartridge 7x20"	4.62
CF07P20M PP	45	35	115	Ø32mm	Ø32mm	Paper 77xØ215	2.30
CF07C30M PP	45	35	145	Ø32mm	Ø32mm	Cartridge 7x30"	6.93
CF07C5M PVDF	45	35	85	Ø32mm	Ø32mm	Cartridge 5x10"	1.65

LENNTECH
WATER TREATMENT Solutions

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289