

Technical data Corode filter unit



CF11..S

11000l/h – Filter housing PP

Corode unit with seal pump **CPS-11**.

Q max :11m³/h

Q min :2.2m³/h

Q nominal :7m³/h

Pump head :PP

Motor : 0.55kW, 400V, 2.3/1.3Amp, 3Ph, 50Hz, IP55

Suitable for hot sealing processes.

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 10", 20"

Standard units include:

Terminal overload protection

Air release and drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 10"xØ310 (18 liter)

20"xØ310 (36 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF11CS PP	55	45	90	Ø38mm	Ø38mm	Cartridge 15x10"	4.95
CF11PS PP	55	45	90	Ø38mm	Ø38mm	Paper 37xØ295	2.20
CF11C20S PP	55	45	115	Ø38mm	Ø38mm	Cartridge 15x20"	9.90
CF11P20S PP	55	45	115	Ø38mm	Ø38mm	Paper 66xØ295	4.30
CF11C7S PP	55	45	115	Ø38mm	Ø38mm	Cartridge 7x20"	4.62
CF11P7S PP	55	45	115	Ø38mm	Ø38mm	Paper 77xØ215	2.30



info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289