

Technical data Corode filter unit



CF20..S

21000l/h – Filter housing PP

Corode unit with seal pump **CPS-20**.

Q max :20m³/h

Q min :4m³/h

Q nominal :14m³/h

Pump head :PP

Motor : 1.5kW, 400V, 5.4/3.2Amp, 3Ph, 50Hz, IP55

Suitable for hot sealing processes.

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 20", 30"

Standard units include:

Terminal overload protection

Air release and drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 20"xØ310 (36 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF20CS PP	60	50	120	Ø50mm	Ø50mm	Cartridge 15x20"	9.90
CF20PS PP	60	50	120	Ø50mm	Ø50mm	Paper 66xØ295	4.30
CF20C30S PP	60	50	145	Ø50mm	Ø50mm	Cartridge 15x30"	14.85
CF20P30S PP	60	50	145	Ø50mm	Ø50mm	Paper 95xØ295	6.45



info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289