

Technical data Corode filter unit



FIL11..M

12000l/h – Filter housing PP or PVDF material

Corode unit with magnetic drive pump **MAG-10**.

Q max :12m³/h

Q min :1m³/h

Pump head :PP or PVDF

Motor :0.55kW, 400V, 2.29/1.32Amp, 3Ph, 50Hz,

IP55 :0.55kW, 230V, 5Amp, 1Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C

Filter housing in PVDF maximum temp 100°C

Outside metal SS316

Height filter housing: 10", 20"

Standard units include:

Thermal overload switch

Air release/ drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 10"xØ310 (18 liter)

20"xØ310 (36 liter)



	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
FIL11CM PP	55	45	90	Ø38mm	Ø38mm	Cartridge 15x10"	4.95
FIL11PM PP	55	45	90	Ø38mm	Ø38mm	Paper 37xØ295	2.20
FIL11C20M PP	55	45	115	Ø38mm	Ø38mm	Cartridge 15x20"	9.90
FIL11P20M PP	55	45	115	Ø38mm	Ø38mm	Paper 66xØ295	4.30
FIL11C7M PP	55	45	115	Ø38mm	Ø38mm	Cartridge 7x20"	4.62
FIL11P7M PP	55	45	115	Ø38mm	Ø38mm	Paper 77xØ215	2.30
FIL11C52M PVDF	55	45	115	Ø38mm	Ø38mm	Cartridge 5x20"	1.65



info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289