

Technical data Corode filter unit



FIL20..M

23000l/h – Filter housing PP

Corode unit with magnetic drive pump **MAG-20**.

Q max :23m³/h

Q min :4m³/h

Pump head :PP

Motor : 1.1kW, 400V, 3.97/2.29Amp, 3Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C

Outside metal SS316

Height filter housing: 20", 30"

Standard units include:

Thermal overload switch

Air release/ drain valve

Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector

Hand priming pump

Transport wheels

Precoat tank PP 20"xØ310 (36 liter)



	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
FIL20CM PP	60	50	120	Ø50mm	Ø50mm	Cartridge 15x20"	9.90
FIL20PM PP	60	50	120	Ø50mm	Ø50mm	Paper 66xØ295	4.30
FIL20C30M PP	60	50	145	Ø50mm	Ø50mm	Cartridge 15x30"	14.85
FIL20P30M PP	60	50	145	Ø50mm	Ø50mm	Paper 95xØ295	6.45



info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289