




DOWEX Ion Exchange Resins

The Removal of Oxygen and Chlorine from Water

The Removal of Oxygen

Dissolved oxygen can be reduced by using sodium sulfite according to following reaction:



Based on this equation, a minimum of 7.87 mg Na_2SO_3 is necessary per mg dissolved O_2 . The table shows levels required to remove different amounts of dissolved oxygen:



Dissolved Oxygen		Sodium Sulfite (theoretical amount)	
cc/liter**	mg/l	mg/l	lbs/ 1000 gal.
0.1	0.14	1.1	0.0094
0.2	0.29	2.3	0.019
0.3	0.43	3.4	0.028
0.4	0.57	4.5	0.038
0.5	0.72	5.6	0.047
1.0	1.4	11.3	0.094
2.0	2.9	22.5	0.19
5.0	7.2	56.3	0.47
10.0	14.3	112.5	0.94

**1 cc dissolved oxygen per liter = 1.43 mg/l

1 mg/l dissolved oxygen = 0.698 cc/liter

The Removal of Chlorine

Chlorine is a strong oxidant and may readily degrade ion exchange resins. Chlorine levels in water can be reduced using sulphur dioxide or sodium sulphite according to following reactions:



Per gram of chlorine to remove, one needs to add a minimum of 0.91 gram of SO_2 or 1.78 gram of Na_2SO_3 . This leads to following amounts of reducing agents to add per 1000 liter of water for the given chlorine levels:

Cl_2 mg/l	Na_2SO_3 (theoretical amount)		SO_2 (theoretical amount)	
	g/1000 l	lbs/1000 gal.	g/1000 l	lbs/ 1000 gal.
0.1	0.18	0.0015	0.09	0.00075
0.5	0.89	0.0075	0.45	0.0038
1	1.78	0.015	0.91	0.0075
2	3.56	0.030	1.82	0.015
3	5.34	0.045	2.73	0.0225
4	7.12	0.06	3.64	0.03
5	8.90	0.075	4.55	0.038
10	17.80	0.15	9.10	0.075

*Trademark of The Dow Chemical Company

DOWEX

Ion Exchange Resins

LENNTECH

info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289

WARNING: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Published May 2002.

