DuPont™ Electrodeionization (EDI) Module

Model: EDI-830

Key Features

- Premium ion exchange resins in the EDI modules can provide consistent high-purity water production while reducing operating resistance and improving efficiency.
- The three-outlet configuration, featuring a dedicated electrode water outlet, can improve electrolyte control and supports higher overall water recovery.
- Integrated plate-and-frame sealing helps enhance reliability.
- Compact, stackable design reduces footprint requirements.
- No chemical regeneration for easier operation and maintenance.

Key Applications

Ideal for high-purity and ultrapure water applications across various industries:

- Power generation and green hydrogen.
- Chemical, coal to chemical, and petrochemical.
- Metallurgy, such as steel and non-ferrous metals.
- Microelectronics, such as solar photovoltaic and semiconductor chips assembly and test.
- Light industries such as pulp and paper.

Typical Properties


Model	Nominal Product Water Flow Rate (m^3/h)	Product Water Resistivity [1,2] (MΩ · cm)	Silica (as SiO_2) Removal [2]
EDI-830	8	≥16	90-99%

[1] Test condition: Feed water conductivity 20μS/cm NaCl, 77°F (25°C) and 90% recovery.
[2] Actual performance depends on project-specific feedwater quality and operating conditions.


Product Parameters

Model	Dilute Inlet and Outlet Connections		Concentrate Inlet and Outlet Connections		Electrolyte flush Connections		Dimensions			Mounting	Weight
	Size	Type	Size	Type	Size	Type	W mm/in	H mm/in	D L1 mm/in	L2 mm/in	(kg/lb)
EDI-830	Φ 32	Male Adapter	Φ 20	Male Adapter	Φ 10	Push-in fitting	300/11.8	610/24.0	815/32.1	800/31.5	176/388






Front view



Left view



Top view

Form No. 45-D05248-en, Rev. 0
October 2026

Feedwater Quality Specifications

Index	Parameter
Feed water source[3]	RO permeate
FCE[4]	≤ 40 µS/cm
Hardness (as $CaCO_3$)[5]	≤ 1.0 ppm
pH (operating range)	5–9
Silica (SiO_2)[6]	≤ 1.0 ppm
Total organic carbon (TOC)	≤ 0.5 ppm
Total chlorine (as Cl_2)	≤ 0.05 ppm
Fe, Mn, H_2S	≤ 0.01 ppm
SDI_{15}	< 1.0
Oil/grease (mg/L)	Not detectable
Oxidants (mg/L)	Not detectable
Color (APHA)	<5.0

Operating Conditions

Index	SI Units	US Units
Dilute stream product flow	4.0–11.5 m^3/h	17.6–50.6 gpm
Recovery	Up to 95%	
Feedwater temperature	5–40 °C	41–104 °F
Feedwater pressure (maximum)	6.9 bar	100 psig
Dilute pressure drop[7]	2.0–3.2 bar	29–46.5 psig
Dilute outlet pressure more than concentrate outlet pressure	0.35–0.7 bar	5–10 psig
Operating current (maximum)	5.2 A	
Operating voltage (maximum)	400 VDC	

[3] Typically feed water source is 2nd pass RO permeate.
[4] FCE (Feed Conductivity Equivalent) includes conductivity, CO_2, and SiO_2.
[5] Typically feed hardness is ≤ 0.1 ppm as $CaCO_3$.
[6] Typically feed silica is ≤ 0.2 ppm as SiO_2.
[7] At nominal flow rate and 25 °C.

Important Information

Proper startup of the EDI system is essential to condition the module for operation and prevent damage. Before starting the EDI system, confirm that all instrument calibrations and system checks have been completed and that the RO permeate quality meets the EDI operating requirements. If a buffer tank is used, ensure that the tank, all piping, and all headers leading to the EDI modules have been thoroughly flushed before startup. For more information, refer to the DuPont™ EDI product manual. DuPont™ EDI modules are designed to deionize RO permeate and must be operated within the feedwater specifications listed above. Failure to strictly follow the operating limits and guidelines in this document will avoid the limited warranty. Refer to the DuPont™ EDI product warranty terms for details.

Operating Guidelines

Hydrogen, oxygen, and chlorine are generated at the electrodes through water electrolysis and are discharged with the concentrate stream. These gases must be properly vented to prevent accumulation. EDI modules are sensitive to particulate contamination; blockage within the resin bed increases pressure drop and can immediately affect demineralization performance. Oxidizing agents, such as chlorine, attack ion exchange membranes and resin beads and may cause irreversible damage.

Product Stewardship

DuPont is committed to the safety of all those who manufacture, distribute, and use its products, as well as to protecting the environment on which we all depend. This commitment forms the basis of our product stewardship philosophy: we assess product safety, health, and environmental information and take appropriate steps to protect employees, the public, and the environment. The success of product stewardship depends on everyone involved throughout the life cycle of DuPont products—from initial concept and research through manufacture, use, sale, disposal, and recycling.

Customer Notice

DuPont strongly recommends that customers review their manufacturing processes and applications of DuPont products from the perspectives of human health and environmental quality to ensure that DuPont products are not used in ways for which they were not intended or tested. DuPont personnel are available to answer questions and provide reasonable technical support. DuPont product literature, including safety data sheets, should be consulted before using DuPont products.

Important Notice

This product is not intended for drinking water applications.

DUPONT™

Have a question? Contact us at:
info@lenntech.com

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2026 DuPont. All rights reserved

Form No. 45-D05248-en, Rev. 0
October 2026