

DuPont™ Inge™ MB 1.5 XL 40 Module

Modules for Open Platform

Key Features

Proven Multibore™ PES Fibers:

- Exceptional physical strength and chemical resistance.
- High colloidal particulate, bacteria and virus log removal rate.
- Unique design for high solids loads.
- Optional coagulation can enhance the removal of algae and organics.

Optimized Module Design:



- Open platform design to fit customer built skids.
- Robust materials for long lifetime.
- Easy installation and low maintenance.
- All wetted parts corrosion free.

Key Applications

- Municipal wastewater.
- Industrial water.
- Wastewater reuse.
- Ideal for height restricted or containerized filtration solution.

Module Specification

General		
Part Number / GMID	IN-0069 / 12071517	
Mode of Filtration	In-Out Pressurized	
Membrane Type	Multibore™	
Membrane Material	PESm	
Nominal Membrane Pore Size	0.02 µm	
Module Operating Process	Dead-end	
Housing Material	PVC-U, white	
End Cap Material	PVC-U, grey	
End Cap Coupling Material	SS (EPDM sealing)	
Dimensions		
Active Membrane Area	40 m²	431 ft²
Module Length (L)	1,485 ± 1.5 mm	58.5 inch
Distance Top / Bottom Feed Port (L1)	1,599 ± 3.0 mm	63.0 inch
Length with End Caps (L2)	1,679 ± 3.0 mm	66.1 inch
Module Diameter (A)	250 ± 1.5 mm	9.8 inch
Distance Feed Top Port - Filtrate Port (B)	190 ± 1.5	7.5 inch
Outer Diameter End Cap Coupling Maximum (C)	295 mm	11.6 inch
Protruding Part of the Port (E)	40 ± 1 mm	1.6 inch
Filtrate / Backwash Port (D)	50.8 mm	2 inch
Weight and Volume		
Shipping Weight	43 kg	95 lbs.
Weight Empty	43 kg	95 lbs.
Weight Filled	95 kg	209 lbs.
Hold-Up Volume Feed (CIP)	20 L	5.4 gal
Hold-Up Volume Membrane Structure (CIP)	16 L	4.2 gal
Hold-Up Volume Filtrate (CIP)	25 L	6.8 gal



Certified to NSF/ANSI/CAN 61
& NSF/ANSI 419

Suggested Operating Conditions

General	Details	
Operating Temperature Range	1 - 45 °C	34 - 113 °F
Operating pH	2 - 12	
Cleaning pH	1 - 13	
Typical Filtration TMP	0.1 - 0.6 bar	1.5 - 8.7 psi
Typical Backwash TMP	0.3 - 2.0 bar	4.4 - 29.0 psi
Backwash Flux	230 L/(m²h)	135 gfd
Backwash Flow	9.2 m³h	40.5 gpm
Operating Limits (Maximum)		
Rate of Temperature Change	5 °C/min	9 °F/min
Inlet Pressure at max 40°C	5 bar	73 psi
Rate of Pressure Change	0.5 bar/sec	7.3 psi/sec
Filtration TMP	1.5 bar	22 psi
Backwash TMP	3.0 bar	44 psi
Filtration Flux	180 L/(m²h)	106 gfd
Filtration Flow	7.2 m³h	31.7 gpm
Backwash Flux	300 L/(m²h)	176 gfd
Particle Size	300 µm	
Exposure NaOCl*	≤ 500,000 ppm x h (at pH ≥ 9.5)	
Concentration NaOCl	2,000 ppm	

*NaOCl exposure limits at lower pH are dependent on water type and are project specific.

General Information

- Avoid any abrupt pressure variations during start-up, operation, shutdown, cleaning or other sequences to prevent possible membrane damage. The maximum pressure change allowable is 0.5 bar/s.
- For assembly, please refer to the latest version of the [DuPont™ Inge™ Open Platforms PES-UF Modules Assembly Manual](#) (Form No. 45-D02231-en).
- If operating limits and guidelines given in this bulletin are not strictly followed, any warranty will be null and void.
- To control biological growth during extended system shutdowns, a storage solution must be introduced into the membrane modules. For Detailed information, see the [DuPont™ Inge™ PES-UF Module Preservation Instruction](#) (Form No. 45-D02946-en).

Regulatory Note

- Certified drinking water modules require specific conditioning procedures prior to producing potable water. For operating parameters, please refer to the [DuPont™ Inge™ Process and Design Guidelines](#) (Form No. 45-D02234-en).
- Drinking water modules may be subjected to additional regulatory restrictions in some countries. Please check local regulatory guidelines and application status before use.
- Flushing needs to be done according to the [DuPont™ Inge™ PES-UF Module Rinsing Procedure](#) (Form No. 45-D02947-en).



info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

