

DuPont™ Inge™ MB PRO L 72 S Module

Modules Installed in Inge™ Submerged MB Rack

Key Features

Innovative Multibore™ PRO PES Fibers:

- Exceptional physical strength and chemical resistance.
- High colloidal particulate, bacteria and virus log removal rate.
- Excellent filtration permeability.
- Optional coagulation can enhance the removal of algae and organics.



Optimized Module Design:

- Ideal design to integrate in Submerged MB Rack.
- Enhanced active filtration area.

Key Applications

- Municipal drinking water.
- Desalination RO pretreatment.
- Ideal to replace submerged filtration systems.

MB PRO



Module Specification

General		
Part Number / GMID	IN-6131 / GMID 12117573	
Mode of Filtration	In-Out Submerged	
Membrane Type	Multibore™ PRO	
Membrane Material	PESm	
Nominal Membrane Pore Size	0.02 µm	
Module Operating Process	Dead-end	
Housing Material	PVC-U, white	
Dimensions		
Active Membrane Area	72 m²	775 ft²
Module Length (L)	1720 mm	67.7 inch
Module Diameter (D)	220 mm	8.7 inch
Filtrate Diameter (d)	42.8 mm	1.7 inch
Weight and Volume		
Shipping Weight (Module Only)	33 kg	72 lbs.
Weight Empty	33 kg	72 lbs.
Weight Filled	74 kg	164 lbs.
Hold-Up Volume Feed (CIP)	13 L	3.4 gal
Hold-Up Volume Membrane Structure (CIP)	13 L	3.4 gal
Hold-Up Volume Filtrate (CIP)	24 L	6.3 gal

Suggested Operating Conditions

General	Details	
Operating Temperature Range	1 - 45 °C	34 - 113 °F
Operating pH	2 - 12	
Cleaning pH	1 - 13	
Typical Filtration Trans-Membrane Pressure (TMP)	0.1 - 0.5 bar	1.5 - 7.3 psi
Typical Backwash TMP	0.3 - 1.5 bar	4.4 - 21.8 psi
Backwash Flux	230 L/(m²h)	136 gfd
Backwash Flow	16.6 m³/h	73 gpm
Operating Limits (Maximum)		
Rate of Temperature Change	5 °C/min	9 °F/min
Rate of Pressure Change	0.5 bar/sec	7.3 psi/sec
Filtration TMP	0.7 bar	10.2 psi
Backwash TMP	3.0 bar	44 psi
Filtration Flux	140 L/(m²h)	82 gfd
Filtration Flow	10.1 m³/h	44.4 gpm
Backwash Flux	250 L/(m²h)	147 gfd
Particle Size	230 µm	
Exposure NaOCl*	≤ 500,000 ppm x h (at pH ≥ 9.5)	
Concentration NaOCl	2,000 ppm	

*NaOCl exposure limits at lower pH are dependent on water type and are project specific.

General Information

- Avoid any abrupt pressure variations during start-up, operation, shutdown, cleaning or other sequences to prevent possible membrane damage. The maximum pressure change allowable is 0.5 bar/s.
- For assembly, please refer to the latest version of the [DuPont™ Inge™ Submerged Multibore™ Rack Assembly Manual](#) (Form No. 45-D04906-en).
- If operating limits and guidelines given in this bulletin are not strictly followed, any warranty will be null and void.
- To control biological growth during extended system shutdowns, a storage solution must be introduced into the membrane modules. For Detailed information, see the [DuPont™ Inge™ PES-UF Module Preservation Instruction](#) (Form No. 45-D02946-en).

Regulatory Note

- Certified drinking water modules require specific conditioning procedures prior to producing potable water. For operating parameters, please refer to the [DuPont™ Inge™ Process and Design Manual for Submerged Modules](#) (Form No. 45-D04909-en).
- Drinking water modules may be subjected to additional regulatory restrictions in some countries. Please check local regulatory guidelines and application status before use.
- Flushing needs to be done according to the [DuPont™ Inge™ PES-UF Module Rinsing Procedure](#) (Form No. 45-D02947-en).



info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289



All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2026 DuPont. All rights reserved

Form No. 45-D04797-en, Rev. 2
January 2026