




TOPCART Cartridge filter TKF-610 / 620 / 630 / 640-AD10-050D



Specification*	TKF-610-AD10-050D	TKF-620-AD10-050D	TKF-630-AD10-050D	TKF-640-AD10-050D
Code No.	F650302	F650303	F650304	F650305
Material housing	1.4408 (CF8M) 1.4571 (SS316Ti)	1.4408 (CF8M) 1.4571 (SS316Ti)	1.4408 (CF8M) 1.4571 (SS316Ti)	1.4408 (CF8M) 1.4571 (SS316Ti)
Material gasket	NBR-O-Ring **	NBR-O-Ring **	NBR-O-Ring **	NBR-O-Ring **
Max. Operating Pressure [bar]	10	10	10	10
Max. Operating Temperature [°C]	160	160	160	160
Connections N1/N2	DN 50 / PN 16	DN 50 / PN 16	DN 50 / PN 16	DN 50 / PN 16
Vent (N3/N4)	2 x ISO 228-1 – G 1/4"	2 x ISO 228-1 – G 1/4"	2 x ISO 228-1 – G 1/4"	2 x ISO 228-1 – G 1/4"
Drain (N5/N6)	2 x ISO 228-1 – G 1/2"	2 x ISO 228-1 – G 1/2"	2 x ISO 228-1 – G 1/2"	2 x ISO 228-1 – G 1/2"
Weight [kg]	42	46,5	50,7	55
Volume [L]	16	24	32	40
Cartridge length	9 3/4" = 248 mm 10" = 254 mm	19 1/2" = 495 mm 20" = 508 mm	29 1/4" = 743 mm 30" = 762 mm	39" = 991 mm 40" = 1016 mm
Cartridge outer diameter	max. 64 mm			
Cartridge type	DOE / SOE 222	DOE / SOE 222	DOE / SOE 222	DOE / SOE 222
Dimension L1 [mm]	539	793	1047	1301

* Changes possible w/o notice

** Optional EPDM, FPM