

Domestic single pump boosting units

Applications

Automatic supply of water whilst maintaining constant system pressure.

Configuration

These domestic booster units can be built in various configurations using different types of pumps, larger vessels and alternative control devices.

For further assistance/selection please contact our sales team.



Technical features

Model	Code		P2		Size		Vessel Position	Code
	With Vessel	With Pressdrive 05	[kW]	[HP]	Vessel	Pressdrive		
Delta 505		D505/05	0.37	0.5	8 ltr	05	Vertical	50505
Delta 505	D505/24		0.37	0.5	24 ltr		Horizontal	75524
Delta 755		D755/05	0.5	0.75	8 ltr	05	Vertical	75505
Delta 755	D755/24		0.5	0.75	24 ltr		Horizontal	75524
Delta 1005		D1005/05	0.75	1	8 ltr	05	Vertical	100505
Delta 1005	D1005/24		0.75	1	24 ltr		Horizontal	100524
Delta 1755		D1755/05	0.75	1	8 ltr	05	Vertical	175505
Delta 1755	D1755/24		0.75	1	24 ltr		Horizontal	175524
Tecno 25.3		T25.3/05	0.75	1	18 ltr	05	Vertical	25305
Tecno 25.3	T25.3/24		0.75	1	24 ltr		Horizontal	25324
Tecno 25.4		T25.4/05	0.9	1.25	18 ltr	05	Vertical	25405
Tecno 25.4	T25.4/24		0.92	1.25	24 ltr		Horizontal	25424
Tecno 25.5		T25.5/05	1.1	1.5	18 ltr	05	Vertical	25505
Tecno 25.5	T25.5/24		1.1	1.5	24 ltr		Horizontal	25524
Aspri 35.3	C35.3/24		1.1	1.5	24 ltr		Horizontal	35324
Aspri 35.3		C35.3/05	1.1	1.5		05		35305
Aspri 35.4	C35.4/24		1.5	2	24 ltr		Horizontal	35324
Aspri 35.4		C35.3/05	1.5	2		05		35305

(You must fit a pressure vessel on the discharge pipework for every Acuapres)
(Minimum size is 24 ltrs)