

Multi-Stage Seawater (MSS™) Pump

Operating Parameters

Model *	MSS-15	
Liquid	Seawater, Brackish water, Fresh Water	
Pump Operating Ambient Temp	33 - 158 °F	0.6 - 70.0 °C
Maximum Storage Temp	185 °F	85.0 °C
Pump Operating Flow Range**	33-90.3 gpm	7.5-20.5 m³/h
Maximum Operating Pressure	1200 psi	83 bar
Nominal Sound	<85 bBA	
Nominal Vibration	0.05"/sec - 0.15"/sec	
Filtration Requirement	20 microns	

* Subject to international patent applications

** Range may vary

Performance

Efficiency (Transfer)	Up to 65%
-----------------------	-----------

Materials

Shaft	Duplex SS S31803 ASTM A276/479
Shell	Duplex SS S31803 ASTM A276/479
Shell Bolting	316 SS S31600 ASTM A193/A320/F593
Inlet/ Discharge	Duplex SS S31803 ASTM A276/479
Impellers/ Diffusers	Passivated & Electropolished 316L SS S31603 ASTM A276/479
Motor Adapter	Anodized 713 aluminum A07130 ASTM ZC81A
Motor Coupling	Flexible Disc-FNC Treated Carbon Steel S45C ASTM 1045
Coupling Guard	316L S31603 ASTM A276/479
Pump Leveling Foot	Carbon Steel - A36 Painted ASTM A36
Bearing Drain Line/ Throttle Nipple	Super Duplex SS S32750 ASTM A276/479
Mechanical Seal	316 Carbon Silicon Carbide Buna N FITS ISO DIN/ANSI TYPE 2100
O-Rings	Buna N®
Baseplate	Carbon Steel - A36 Painted ASTM A36
Crating/Packaging	Export-Wood

Options

Inlet placement available in 90° Increments.
High pressure inlet and seal package available

Outline

Each MSS model is custom designed to specific customer requirements.

Packaging/ Crating

Protective Covers	Standard
Export Crating	Standard
Additional Shipping Options	Available per customer requirements
Unit Weight (Dry)	Contact FEDCO for design weight

Hydraulic Design

Pump	Horizontal multi-stage centrifugal pump with barrel flanged joint construction. Single or dual shell.
------	---

Fittings

Pipe Joints	Feed Inlet 3" Cut Groove Feed Outlet 3" Cut Groove
-------------	---

Drive

Motor	Available per customer specific requirements NEMA Frame Standard, IEC Available
-------	--

Bearings

Thrust	FEDCO Water Bearing™ Product Lubricated
Cooling	Product fluid
Lubrication	Product fluid

Testing and Inspection

Performance Test * Hydraulic Institute (HI) Hydrostatic & Centrifugal Pump Testing Standards	Standard
Hydrostatic Test * Hydraulic Institute (HI) Hydrostatic & Centrifugal Pump Testing Standards	Standard
Visual/ Dimension Check	Optional
Sound Test	Optional
Vibration Test	Optional
Witness Test	Optional
Certified Test Data	Optional
Material Certificates	Optional

* General Code Groups, Associations, Laboratories, and Approval Bodies include the American Society for Testing and Materials (ASTM), the International Organization for Standardization (ISO), and the NSF International.



LENNTECH
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

NOTE: All numeric values are based on performance norms. Specific performance data is included with each individual unit. FEDCO reserves the right to make specification changes at any time without prior notice. Please contact your FEDCO representative for information. email: sales@fedco-usa.com

The information, date and drawings in this proposal are strictly confidential and for the use of the Fluid Equipment Development Company, LLC ("FEDCO") and its intended recipient(s) only. The information is not to be disclosed or distributed to any other party(ies) without expressed prior written permission of FEDCO.