

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT O.D. (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4I rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature		
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F
	ESPA1	Saving Energy	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.3	99.0			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA-2514	Saving Energy	250	0.9	14	35.6	2.4	6.10	0.75	1.9	99.4	98.0			1.0	0.5	5	0.5	300	20.68	113	45.0	
	ESPA-2521	Saving Energy	350	1.3	21	53.3	2.4	6.10	0.75	1.9	99.4	98.0			2.0	0.9	9.9	0.9	300	20.68	113	45.0	
	ESPA-2540	Saving Energy	750	2.8	40	101.6	2.4	6.10	0.75	1.9	99.4	98.0			4.0	1.8	25.5	2.4	300	20.68	113	45.0	
	ESPA-4014	Saving Energy	500	1.9	14	35.6	3.95	10.03	0.75	1.9	99.4	98.0			3.1	1.4	16.9	1.6	300	20.68	113	45.0	
	ESPA-4021	Saving Energy	1000	3.8	21	53.3	3.95	10.03	0.75	1.9	99.4	98.0			4.0	1.8	29	2.7	300	20.68	113	45.0	
	ESPA-4611	Saving Energy	930	3.5	11.3	28.7	4.6	11.68	0.75	1.9	99.4	98.0			11.0	5.0	31	2.9	300	20.68	113	45.0	
	ESPA-4641	Saving Energy	3600	13.6	41.3	104.9	4.6	11.68	0.75	1.91	99.4	97.5			11.0	5.0	120	11.1	300	20.68	113	45.0	
	ESPA-50	Saving Energy	50	0.2	11.74	29.8	1.78	4.52	0.68	1.7	99.0				0.5	0.23			300	20.68	113	45.0	
	ESPA-75	Saving Energy	75	0.3	11.74	29.8	1.78	4.52	0.68	1.7	98.0				0.5	0.23			300	20.68	113	45.0	
	ESPA1-2012	Saving Energy																					
	ESPA1-2521	Saving Energy	350	1.3	21	53.3	2.4	6.1	0.75	1.9	99.4	98.0			2.0	0.9	10	0.9	300	20.68	113	45.0	
	ESPA1-4014	Saving Energy	500	1.9	14	35.6	3.95	10.03	0.75	1.9		98.0			3.1	1.4	17	1.6	300	20.68	113	45.0	
	ESPA1-4040	Saving Energy	2600	9.8	40	101.6	3.95	10.03	0.75	1.9	99.3	99.0			7.9	3.6	85	7.9	600	41.37	113	45.0	
	ESPA1-8040	Saving Energy	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.3	99.0			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA2-4040	Saving Energy	1900	7.2	40	101.6	3.95	10.03	0.75	1.9	99.6	99.4			7.9	3.6	85	7.9	600	41.37	113	45.0	
	ESPA2 LD-4040	Saving Energy	2000	7.5	40	101.6	3.95	10.03	0.75	1.9	99.6	99.4			7.9	3.6	80	7.4	600	41.37	113	45.0	
	ESPA2-LD	Saving Energy	10000	37.7	40	101.6	7.89	20.04	1.125	2.9	99.6	99.4			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA2-8040	Saving Energy	9000	33.9	40	101.6	7.89	20.04	1.125	2.9	99.6	99.5			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA2 MAX-8040	Saving Energy	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.6	99.5			36.2	16.4	440	40.8	600	41.37	113	45.0	
	ESPA3-4040	Saving Energy	3000	11.3	40	101.6	3.95	10.03	0.75	1.9	98.5				5.1	2.3	85	7.9	600	41.37	113	45.0	
	ESPA3-8040	Saving Energy								0.0													
	ESPA4-4040	Saving Energy	2500	9.4	40	101.6	3.95	10.03	0.75	1.9	99.2	99.0			7.9	3.6	85	7.9	600	41.37	113	45.0	
	ESPA4-8040	Saving Energy	12000	45.2	40	101.6	3.95	10.03	1.125	2.9	99.2	99.0			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA4-LD	Saving Energy	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.2	99.0			36.2	16.4	400	37.1	600	41.37	113	45.0	
	ESPA4-MAX	Saving Energy	13200	49.7	40	101.6	7.89	20.04	1.125	2.9	99.2	99.0			36.2	16.4	440	40.8	600	41.37	113	45.0	
	ESPAB MAX	Saving Energy	9000	33.9	40	101.6	7.89	20.04	1.125	2.9	99.3	99.0			36.2	16.4	440	40.8	600	41.37	113	45.0	
	ESPAUP-8040	Saving Energy																					
	CPA2	High Rejection	10000	37.7	40	101.6	7.89	20.04	1.125	2.9	99.7	99.5			36.2	16.4	365	33.9	600	41.37	113	45.0	
	CPA2-4040	High Rejection	2250	8.5	40	101.6	3.95	10.03	0.75	1.9	99.5	99.2			7.9	3.6	85	7.9	600	41.37	113	45.0	
	CPA2-8040	High Rejection	10000	37.7	40	101.6	7.89	20.04	1.125	2.9	99.7	99.5			36.2	16.4	365	33.9	600	41.37	113	45.0	
	CPA3	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	400	37.1	600	41.37	113	45.0	
	CPA3-8040	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	400	37.1	600	41.37	113	45.0	
	CPA3-LD-8040	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	400	37.1	600	41.37	113	45.0	
	CPA4-8040	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4							
	CPA5-LD	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	400	37.1	600	41.37	113	45.0	
	CPA5-LD-4040	High Rejection	2100	7.9	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5			7.9	3.6	80	7.4	600	41.37	113	45.0	
	CPA5-LD-8040	High Rejection	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4							
	CPA5-MAX	High Rejection	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	440	40.8	600	41.37	113	45.0	
	CPA5-MAX-8040	High Rejection	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.7	99.6			36.2	16.4	440	40.8	600	41.37	113	45.0	
	LFC1	Low Fouling	10000	37.7	40	101.6		0.00		0.0		99.0						365	33.9	600	41.37	113	45.0
	LFC3-LD	Low Fouling	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.5			36.2	16.4	400	37.1	600	41.37	113	45.0	
	LFC3-LD-4040	Low Fouling	2100	7.9	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5			7.9	3.6	80	7.4	600	41.37	113	45.0	
	LFC3-LD-8040	Low Fouling	11000	41.4	40	101.6	7.89	20.04	1.125	2.9	99.7	99.5			36.2	16.4	400	37.1	600	41.37	113	45.0	
	LFC2	Low Fouling	11000	41.4	40	101.6						95.0						365	33.9	600	41.37	113	45.0
	LFC1-4040	Low Fouling	2300	8.7	40	101.6						99.0			7.9	3.6	85	7.9	600	41.37	113	45.0	
	LFC2-4040	Low Fouling	2500	9.4	40	101.6	3.95	10.03	0.75	1.9		95.0			7.9	3.6	85	7.9	600	41.37	113	45.0	
	LFC1-8040	Low Fouling																					
	LFC2-8040	Low Fouling																					
	ESNA1-4040	NanoFiltration																					
	ESNA1-LF	NanoFiltration																					
	ESNA1-LF2	NanoFiltration																					
	ESNA1-LF2-LD-8040	NanoFiltration	10500	39.6	40	101.6	7.89	20.04	1.125	2.9	86.0	83.0			36.2	16.4	400	37.1	600				

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT O.D. (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4l rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			gpd	m³ / day	inch	cm	inch	cm	inch	cm	%	%	%	%	lbs	kg	ft²	m²	psi	KPa	°F	°C
SanRO CPA4 4040	Sanitizable	1400	5.3	40	101.6	3.98	10.11	0.75	1.9	99.6					18.3	8.3						
SanRO ESPA2 8040	Sanitizable	13000	49.0	40	101.6	7.9	20.07	1.125	2.9	99.5					77.6	35.2						
SanRO CPA3 8040	Sanitizable	10500	39.6	40	101.6	7.9	20.07	1.125	2.9	99.6					77.6	35.2						
SanRO LFC3 8040	Sanitizable	9000	33.9	40	101.6	7.9	20.07	1.125	2.9	99.6					77.6	35.2						
SanRO CPA4 8040	Sanitizable	5500	20.7	40	101.6	7.9	20.07	1.125	2.9	99.6					77.6	35.2						
DairyUF 5K 3838-30	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		80	7.4	150	10.34	131	52.2
DairyUF 5K 3838-46	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		60	5.6	150	10.34	131	52.2
DairyUF 5K 4336-30	Sanitizable	2097	7.9	35.5	90.2	4.28	10.87	0.83	2.1						0.0		90	8.3	150	10.34	131	52.2
DairyUF 5K 4336-46	Sanitizable	2097	7.9	35.5	90.2	4.28	10.87	0.83	2.1						0.0		70	6.5	150	10.34	131	52.2
DairyUF 5K 6338-30	Sanitizable	4195	15.8	38	96.5	6.36	16.15	1.138	2.9						0.0		200	18.5	150	10.34	131	52.2
DairyUF 5K 6338-46	Sanitizable	4195	15.8	38	96.5	6.36	16.15	1.138	2.9						0.0		150	13.9	150	10.34	131	52.2
DairyUF 5K 8038-30	Sanitizable	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		360	33.4	150	10.34	131	52.2
DairyUF 5K 8038-46	Sanitizable	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		280	26.0	150	10.34	131	52.2
DairyRO 3838-30	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		80	7.4	800	55.16	122	48.6
DairyRO 3838-46	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		60	5.6	800	55.16	122	48.6
DairyRO 3840-30	Sanitizable	1805	6.8	38.75	98.4	3.78	9.60	0.83	2.1						0.0		80	7.4	800	55.16	122	48.6
DairyRO 8038-30	Sanitizable	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		360	33.4	800	55.16	122	48.6
DairyRO 8040-30	Sanitizable	4832	18.2	40	101.6	7.9	20.07	1.125	2.9						0.0		360	33.4	800	55.16	122	48.6
Hydrapolish 8	Sanitizable	4832	18.2	40	101.6	7.9	20.07	1.125	2.9						0.0		360	33.4	800	55.16	122	48.6
DairyUF 10K 3838-30	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		80	7.4	150	10.34	131	52.2
DairyUF 10K 3838-46	Sanitizable	1805	6.8	38	96.5	3.78	9.60	0.83	2.1						0.0		60	5.6	150	10.34	131	52.2
DairyUF 10K 4336-30	Sanitizable	2097	7.9	35.5	90.2	4.28	9.60	0.83	2.1						0.0		90	8.3	150	10.34	131	52.2
DairyUF 10K 4336-46	Sanitizable	2097	7.9	35.5	90.2	4.28	10.87	0.83	2.1						0.0		70	6.5	150	10.34	131	52.2
DairyUF 10K 4338-30	Sanitizable	2097	7.9	38	96.5	4.28	10.87	0.83	2.1						0.0		80	7.4	150	10.34	131	52.2
DairyUF 10K 6338-30	Sanitizable	4195	15.8	38	96.5	6.36	10.87	1.138	2.9						0.0		200	18.5	150	10.34	131	52.2
DairyUF 10K 6338-46	Sanitizable	4195	15.8	38	96.5	6.36	16.15	1.138	2.9						0.0		150	13.9	150	10.34	131	52.2
DairyUF 10K 6338-65	Sanitizable	4195	15.8	38	96.5	6.36	16.15	1.138	2.9						0.0		120	11.1	150	10.34	131	52.2
DairyUF 10K 6338-80	Sanitizable	4195	15.8	38	96.5	6.36	16.15	1.138	2.9						0.0		100	9.3	150	10.34	131	52.2
DairyUF 10K 8038-30	Sanitizable	4832	18.2	38	96.5	7.9	16.15	1.125	2.9						0.0		360	33.4	150	10.34	131	52.2
DairyUF 10K 8038-46	Sanitizable	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		280	26.0	150	10.34	131	52.2
DairyUF 10K 8038-65	Sanitizable	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		215	19.9	150	10.34	131	52.2
SWC-2514	Seawater	110	0.4	14	35.6	2.4	6.10	0.75	1.9	99.4	99.0				1.0	0.45	5	0.5	1000	68.95	113	45.0
SWC-2521	Seawater	220	0.8	21	53.3	2.4	6.10	0.75	1.9	99.4	99.0				2.0	0.9	10	0.9	1000	68.95	113	45.0
SWC-2540	Seawater	520	2.0	40	101.6	2.4	6.10	0.75	1.9	99.4	99.0				4.0	1.8	26	2.4	1000	68.95	113	45.0
SWC-4014	Seawater	370	1.4	14	35.6	3.95	10.03	0.75	1.9	99.4	99.0				3.1	1.4	17	1.6	1000	68.95	113	45.0
SWC-4021	Seawater	640	2.4	21	53.3	3.95	10.03	0.75	1.9	99.4	99.0				4.0	1.8	29	2.7	1000	68.95	113	45.0
SWC1-4040	Seawater	1200	4.5	40	101.6	3.95	10.03	0.75	1.9		99.5				7.9	3.6	85	7.9	1000	68.95	113	45.0
SWC1-8040	Seawater	5000	18.8	40	101.6	7.95	20.19	1.50	3.8		99.5				36.2	16.4						
SWC2-4040	Seawater	1500	5.7	40	101.6	3.95	10.03	0.75	1.9		99.0				7.9	3.6	70	6.5	1000	68.95	113	45.0
SWC2-8040	Seawater	6200	23.4	40	101.6	7.95	20.19	1.50	3.8		99.0				36.2	16.4						
SWC3-8040	Seawater	5900	22.2	40	101.6	7.95	20.19	1.50	3.8	99.6	99.5				36.2	16.4						
SWC4+8040	Seawater	6500	24.5	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWC4B	Seawater	6500	24.5	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWC4B-MAX	Seawater	7200	27.1	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	440	40.8	1200	82.74	113	45.0
SWC4-LD	Seawater	6500	24.5	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWC4-MAX	Seawater	7200	27.1	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	440	40.8	1200	82.74	113	45.0
SWCB-8040	Seawater	6500	24.5	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWCB-MAX-8040	Seawater	1900	7.2	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5				7.9	3.6	440	40.8	1200	82.74	113	45.0
SWC5-4040	Seawater	1900	7.2	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5				7.9	3.6	85	7.9	1200	82.74	113	45.0
SWC5-LD	Seawater	9000	33.9	40	101.6	7.89	20.04	1.13	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWC5-LD-4040	Seawater	1750	6.6	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5				7.9	3.6	80	7.4	1200	82.74	113	45.0
SWC5-MAX	Seawater	9900	37.3	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	440	40.8	1200	82.74	113	45.0
SWC6-4040	Seawater	2500	9.4	40	101.6	3.95	10.03	0.75	1.9	99.7	99.5				7.9	3.6	85	7.9	1000	68.95	113	45.0
SWC6-8040	Seawater	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
SWC6-MAX	Seawater	13200	49.7	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	440	40.8	1200	82.74	113	45.0
SWC6-LD	Seawater	12000	45.2	40	101.6	7.89	20.04	1.125	2.9	99.8	99.7				36.2	16.4	400	37.1	1200	82.74	113	45.0
HYDRACoRe10-3838-30	Process	1832	6.9	38	96.5	3.78	9.60	0.83	2.1						0.0		80	7.4	600	41.37	140	55.8
HYDRACoRe10-3838-46	Process	1832	6.9	38	96.5	3.78	9.60	0.83	2.1						0.0		60	5.6	600	41.37	140	55.8
HYDRACoRe10-3838-65	Process	1832	6.9	38	96.5	3.78	9.60	0.83	2.1						0.0		50	4.6	600	41.37	140	55.8
HYDRACoRe10-8038-30	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		360	33.4	600	41.37	140	55.8
HYDRACoRe10-8038-46	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		280	26.0	600	41.37	140	55.8
HYDRACoRe10-8038-65	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9						0.0		215	19.9	600	41.37	140	55.8
HYDRACoRe10-8040-30	Process	6027	22.7	40	101.6	7.9	20.07	1.125	2.													

Part Number	Model Name / Description	Type	Flow		Length (A)		OUTPUT O.D. (B)		FEED O.D. (C)		Average NaCl rejection	Minimum NaCl rejection	Average MgSO4 rejection	Minimum MgSO4 rejection	Shipping Weight		Membrane Active Area		Max. Pressure		Max. Temperature	
			<i>gpd</i>	<i>m³ / day</i>	<i>inch</i>	<i>cm</i>	<i>inch</i>	<i>cm</i>	<i>inch</i>	<i>cm</i>	%	%	%	%	<i>lbs</i>	<i>kg</i>	<i>ft²</i>	<i>m²</i>	<i>psi</i>	<i>KPa</i>	<i>°F</i>	<i>°C</i>
	HYDRACoRe50-3838-46	Process	1832	6.9	38	96.5	3.78	9.60	0.83	2.1					0.0		60	5.6	600	41.37	140	55.8
	HYDRACoRe50-3838-65	Process	1832	6.9	38	96.5	3.78	9.60	0.83	2.1					0.0		50	4.6	600	41.37	140	55.8
	HYDRACoRe50-8038-30	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9					0.0		360	33.4	600	41.37	140	55.8
	HYDRACoRe50-8038-46	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9					0.0		280	26.0	600	41.37	140	55.8
	HYDRACoRe50-8038-65	Process	4832	18.2	38	96.5	7.9	20.07	1.125	2.9					0.0		215	19.9	600	41.37	140	55.8
	HYDRACoRe50-8040-30	Process	6027	22.7	40	101.6	7.9	20.07	1.125	2.9					0.0		360	33.4	600	41.37	140	55.8
	HYDRACoRe50-8040-46	Process	4832	18.2	40	101.6	7.9	20.07	1.125	2.9					0.0		280	26.0	600	41.37	140	55.8
	HYDRACoRe50-8040-65	Process	4832	18.2	40	101.6	7.9	20.07	1.125	2.9					0.0		215	19.9	600	41.37	140	55.8
	HYDRACoRe70pHT-4040-46	Process	1805	6.8	40	101.6	3.98	10.11	0.75	1.9					0.0		70	6.5	600	41.37	158	62.9
	HYDRACoRe70pHT-8038-46	Process	1805	6.8	40	101.6	7.9	20.07	1.125	2.9					0.0		275	25.5	600	41.37	158	62.9
	SuPRO 8338-60	Process	1805	6.8	38	96.5	8.35	21.21	1.138	2.9					0.0		222	20.6	200	13.79	158	62.9
	SuPRO 8338-80	Process	1805	6.8	38	96.5	8.35	21.21	1.138	2.9					0.0		184	17.1	200	13.79	158	62.9
	SuPRO 8338-100	Process	1805	6.8	38	96.5	8.35	21.21	1.138	2.9					0.0		155	14.4	200	13.79	158	62.9
	HYDRAcap-40	UltraFiltration	27000	101.7	47 1/4	120.0	2.00	5.08	2.00	5.08					61.7	28.0	320	29.7	73	5.03	104	41.4
	HYDRAcap40-LD	UltraFiltration	27000	101.7	43	109.2	46.125	117.16	47.25	120.0					61.7	28.0	320	29.7	73	5.03	104	41.4
	HYDRAcap MAX-40	UltraFiltration	34800	131.1	53.74	136.5	2.00	5.08	2.00	5.08					161.0	73.0	560	51.9	73	5.03	104	41.4
	HYDRAcap-60	UltraFiltration	42400	159.8	67.25	170.8	2.00	5.08	2.00	5.08					97.0	44.0	500	46.4	73	5.03	104	41.4
	HYDRAcap60-LD	UltraFiltration	27000	101.7	67.25	170.8	2.00	5.08	2.00	5.08					97.0	44.0	323	30.0	73	5.03	104	41.4
	HYDRAcap MAX-60	UltraFiltration	54500	205.4	72.15	183.3	2.00	5.08	2.00	5.08					220.5	100.0	840	77.9	73	5.03	104	41.4
	HYDRAcap-80	UltraFiltration	57000	214.8	87.25	221.6	2.00	5.08	2.00	5.08					119.1	54.0	670	62.1	73	5.03	104	41.4
	HYDRAcap-MAX-80	UltraFiltration	73500	277.0	92.15	234.1	83.11	211.10	87.90	223.3					260.2	118.0	1130	104.8	73	5.03	104	41.4