


Ultrafiltration element

350 UF/MB/TAP





Ultrafiltration element

350 UF/MB/TAP

Specifications 350 UF/MB/TAP		SI		US	
Element data					
Material housing			PVC		PVC
Material connector			PVC		PVC
Housing length	mm	500	+/- 2,0	inch	20
Element length**	mm	603	+/- 3,0	inch	24
Element length	mm	664	+/- 3,0	inch	26
Distance permeate connector-feed connector**	mm	145	+/- 1,0	inch	6
Distance permeate connector-feed connector	mm	224	+/- 1,0	inch	9
Distance permeate connector-element center	mm	73	+/- 2,0	inch	161
Permeate connection male OD		1"			1"
Feed connection male OD		1"			1"
Housing OD	mm	75		inch	3
Element OD	mm	90		inch	4
Endcaps ID**	mm	40		inch	2
Weight	kg	1,5		lbs	3
Membrane Type					
Material			PES		PES
Type			SevenBore®		SevenBore®
Diameter bores ID	mm	0,9		inch	0,04
Diameter fiber OD	mm	4,0		inch	0,16
MWCO		kD 100-150			kD 100-150
Area	m²	1,25		ft²	13
Typical Process Conditions					
Maximum operating temperature	°C	40		°F	104
Maximum system pressure	bar	10		psi	145
Trans membrane pressure operation	bar	< 1,0		psi	< 14,5
maximum	bar	2,5		psi	36
Productivity clean water at 25° C (77°F)	l/m²barh	1300-1600		gfd/psi	53-65
process	l/m²h	100 to 350		gfd	60 to 210
backwash/forward flush	l/m²h	250		gfd	150
Permeate flow at 100 l/m² h	l/h	125		gpm	1
pH range during operation		3-10			3-10
Cleaning					
Soaking time during cleaning		min 5			
pH range during cleaning		1-13			
Disinfecting chemicals	hypochlorite (NaOCl)	ppm 50-200			
	hydrogenperoxide (H₂O₂)	ppm 100-200			

** without screw ends (provided separately)

modifications reserved

LENNTECH
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

IMT
revision februari 2011