



Mounts are options and not included in vessel supply

Note:
Dimensions may be subject to be changed.
Not to be used for construction unless certified.

Please ask for information about available ports

The optional Feed/Brine ports can be used up to 21bars(300PSI) with SS inserts
If you intend to use PVC piping check pipe manufacturers pressure rating
We have PVC inserts available

Max: Working Pressure (bar/PSI)	42 /600
Max. Working Temp. (°C / °F)	60 /150
Min. Working Temp. (°C / °F)	2 / 36
Max Test Pressure (ASMEX) (bar/PSI)	54.6/780

LENNTECH
info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

REF	PART NAME	PART #	MATERIAL
1	SHELL		FRP
2	LINER		PVC
3	GROOVERING		Alu
HEAD			
4	ENDPLATE open	74EP4	PPE
4.1	ENDPLATE closed	74PEP4-C	PPE
9.2	ELEMENT ADAPTER closed	74AD192-C	PPE
5	RETAINING RING	64SEC4	316TI
6.1	SCREW M6	58SCR6x12	316TI
7	O-RING	OR92x5	EPDM
PORTS			
8	HP-PORT (optional)		
10	PERMEATE PORT (optional)		
SUPPORT			
11	MOUNT (optional)	64MOUNT	PE

600 PSI		<i>AnyChem</i> TM Pressure Vessels by Knappe Composites	
Eng.Mgr.	Q.Ass.Mgr.		
SIG:	SIG:	DATUM:	REV:
		23.01.07	1
		<i>AnyChem</i> SERIES 4 inch V4i - FRONT ENTRY	
		Name	Scale:none