

Lewatit® K 1461 is especially suitable for the following applications:

- » Catalysis: Condensations and esterifications of small polar molecules, hydrolysis of ethers and esters
- » Chemicals processing: Decationization of water, removal of heavy metals from solutions, conversion of salts into the free acids

The special properties of this product can only be fully utilized if the technology and process used correspond to the current state-of-the-art. Further advice in this matter can be obtained from Lanxess, Business Unit Ion Exchange Resins.

PRODUCT INFORMATION LEWATIT® K 1461



General Description

Ionic form as shipped	H ⁺
Functional group	sulfonic acid
Matrix	crosslinked polystyrene
Structure	gel type beads
Appearance	light brown, translucent

Physical and Chemical Properties

	metric units	
Total capacity*	min. eq/l	1.8
Uniformity coefficient*	max.	1.1
Mean bead size*	mm	0.62 (+/- 0.05)
Fines	< 0.4 typical:	< 0.1 %
Bulk density	(+/- 5 %) g/l	770
Density	approx. g/ml	1.22
Water retention	wt. %	47 - 53
Stability	temperature range °C	-20 - 130
Storability	of the product max. months	6
Storability	temperature range °C	-20 - 40

* Specification values subjected to continuous monitoring.

Additional Information & Regulations

Safety precautions

Strong oxidants, e.g. nitric acid, can cause violent reactions if they come into contact with ion exchange resins.

Toxicity

The safety data sheet must be observed. It contains additional data on product description, transport, storage, handling, safety and ecology.

Disposal

In the European Community ion exchange resins have to be disposed, according to the European waste nomenclature which can be accessed on the internet-site of the European Union.

Storage

It is recommended to store ion exchange resins at temperatures above the freezing point of water under roof in dry conditions without exposure to direct sunlight. If resin should become frozen, it should not be mechanically handled and left to thaw out gradually at ambient temperature. It must be completely thawed before handling or use. No attempt should be made to accelerate the thawing process.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Edition: 2007-03-29
Previous Edition: 2007-03-29



WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289

For more information or a quote, please use the

Contact Form