

NADIR® UH050 P

Ultrafiltration Membrane



With a nominal molecular weight cut-off (M.W.C.O.) of 50,000 Daltons, NADIR® UH050 flat sheet is a hydrophilic polyethersulfone (PES) membrane that can be configured in a wide variety of element designs for food, dairy and process separations as well as water purification. UH050 membrane sheet is available in dry flat sheet rolls and is FDA compliant.

MEMBRANE CHARACTERISTICS

Membrane Chemistry	Backing Material	Nominal M.W.C.O. (Da)
Polyethersulfone (PES)	Polypropylene	50,000

Permeability LMH/bar (GFD/psi) ^a	Thickness (µm)	pH Range	Chlorine Tolerance ^b
≥ 85.0 (≥ 3.4)	210 – 250	0.0 – 14.0	200 ppm (sanitization) at pH ≥ 10.5

a Test conditions: Clean water, 4 bar (58 psi), 20°C (68°F), crossflow operation. Membrane specifications may change without notice as design revisions occur.

b For daily short term cleaning: maximum 50°C (125°F), 30 min.

IMPORTANT INFORMATION

Standard Sizes: NADIR flat sheet membrane is available in an A4 sample size of 210 mm x 297 mm (8.27 in x 11.69 in) and in a nominal roll size of 150 m x 1016 mm (492 ft x 40.0 in). Custom lengths may be available on request.

Initial Flush: MANN+HUMMEL Water & Fluid Solutions recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

Storage: Membrane shipped dry should be stored away from direct sunlight in a cool, dry place. Please see Membrane Storage Guide – Flat Sheet Membrane (TSG-O-011).

Contact



info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289