

TRISEP® ACMX

Ultra-Low Energy RO Membrane



TRISEP® ACMX flat sheet is an ultra-low energy reverse osmosis membrane that is versatile enough to be used in a wide variety of water purification and process applications. ACMX™ is a new brackish water membrane capable of operating at extremely low pressures to reduce energy costs while delivering unique performance in many applications. ACMX membrane sheet is available in both dry and wet flat sheet rolls and is FDA compliant.

MEMBRANE CHARACTERISTICS

Membrane Chemistry	Backing Material	Stabilized Salt Rejection (%)	Minimum Salt Rejection (%)
Thin-Film Polyamide	Non-Woven Polyester	98.0	97.0

Flux Range LMH (GFD) ^a	Thickness (µm)	pH Range	Chlorine Tolerance ^b
52.6 – 78.1 (31.0 – 46.0)	130 – 170	1.0 – 12.0	< 0.1 ppm

a Test conditions: 500 ppm NaCl, 6.9 bar (100 psi), 25°C (77°F), 15% recovery, pH 8.0, 30 minutes operation. Membrane specifications may change without notice as design revisions occur.

b Oxidizing agents, such as free chlorine, in contact with polyamide membranes may result in shortened operating life or membrane failure.

IMPORTANT INFORMATION

Standard Sizes: TRISEP flat sheet membrane is available in a sample size of 305 mm x 1,016 mm (12 in x 40 in) and in a nominal roll size of 305 m x 1,016 mm (1,000 ft x 40 in). Custom lengths may be available on request.

Initial Flush: MICRODYN-NADIR recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

Storage: Membrane is shipped dry unless wet membrane is specifically requested. Membrane shipped dry should be stored in a cool, dry place. If shipped wet, TRISEP membrane must remain sealed and refrigerated prior to use. Please see Membrane Storage Guide – Flat Sheet Membrane (TSG-O-011).

Contact



info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289

DATE: 02/05/2020

**MANN+
HUMMEL**