

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

Micro-Klean™ D Series Depth Filter Cartridges

A different filter cartridge

Micro-Klean D Series cartridges, formerly known as Micro-Wynd, are produced by an exclusive 3M Purification process which combines 2 separate materials simultaneously on a common core.

The filtering media is applied in blanket form whilst the matrix is wound spirally under controlled tension to bind the media blanket in a firm position.

The winding pattern creates wide diamond shaped chambers which provides the exceptional performances in flow and life time of the Micro-Klean D Series cartridges. With the ordinary wound cartridge, there is no distinct filtering media, the matrix only is operating. It is brushed and separate during the winding operation. This accounts for the shortness of fibres and lack of the very important necessary quantity of matrix, which shortens considerably the life and lowers flow rates.

Multi-length cartridges

To eliminate any chance of by-pass at the cartridge joints, Micro-Klean D Series cartridges can be delivered in several lengths but in one piece construction from 9" $\frac{3}{4}$ to 29". In this case, the media blanket is continuous on the whole length of the cartridge, eliminating overlap winding joints. Integral length cartridges also assure easier and shorter change out.

Operating Conditions

Micro-Klean D Series cartridges are nominally rated (from 1 μ m to 150 μ m nominal). Maximum service temperature can be up to 120 °C depending on the material selected (refer to the specifications of each type). Maximum differential pressure is 5 bar, but it is recommended to replace them at 2.5 bar.

Features and Benefits

Flow capacity up to 3 times higher than the conventional string wound cartridges

- Reduces total filtration costs

Dirt holding capacity up to twice greater

- Reduces total filtration costs

Mechanically able to withstand a very high differential pressure

- Reduces total filtration costs

High dirt removal efficiency

- Reduces total filtration costs

Longer life time

- Less maintenance and production down time
- Decreases waste management costs



Applications

Industrial

- Water
- Acids
- Solvents
- Chemical products
- Etc.

3M

Micro-Klean D Series Cartridges Ordering Guide

PPP TYPE			
Nominal Micron rating (micron)	Simple length (250 mm)	Double length (500 mm)	Triple length (750 mm)
1	D-PPPY	D-PPPY-2	D-PPPY-3
3	D-PPPA	D-PPPA-2	D-PPPA-3
5	D-PPPB	D-PPPB-2	D-PPPB-3
10	D-PPPC	D-PPPC-2	D-PPPC-3
25	D-PPPF	D-PPPF-2	D-PPPF-3
50	D-PPPL	D-PPPL-2	D-PPPL-3
75/150	D-PPPHD	D-PPPHD-2	D-PPPHD-3

CCS TYPE			
Nominal Micron rating (micron)	Simple length (250 mm)	Double length (500 mm)	Triple length (750 mm)
1	D-CCSY	D-CCSY-2	D-CCSY-3
3	D-CCSA	D-CCSA-2	D-CCSA-3
5	D-CCSB	D-CCSB-2	D-CCSB-3
10	D-CCSC	D-CCSC-2	D-CCSC-3
25	D-CCSF	D-CCSF-2	D-CCSF-3
50	D-CCSL	D-CCSL-2	D-CCSL-3
75/150	D-CCSHD	D-CCSHD-2	D-CCSHD-3

CCT TYPE			
Nominal Micron rating (micron)	Simple length (250 mm)	Double length (500 mm)	Triple length (750 mm)
1	D-CCTY	D-CCTY-2	D-CCTY-3
3	D-CCTA	D-CCTA-2	D-CCTA-3
5	D-CCTB	D-CCTB-2	D-CCTB-3
10	D-CCTC	D-CCTC-2	D-CCTC-3
25	D-CCTF	D-CCTF-2	D-CCTF-3
50	D-CCTL	D-CCTL-2	D-CCTL-3
75/150	D-CCTHD	D-CCTHD-2	D-CCTHD-3

Several configurations are possible in combining different materials of the media, matrix and core. Micro-Klean D Series cartridges are available in standard length from 9" ¾ to 29" (integral length) and in DOE version. Longer length (i.e. 40") or SOE versions (with end caps and double o-ring) can be produced upon request.

Depending on the chemical compatibility requested by the application, different configurations can be chosen. However, it is always recommended to check the chemical compatibility by a soaking test in the liquid to be filtered.

PPP TYPE

Polypropylene media, matrix and core.

Cartridge for applications involving strong acid, concentrated alkalis, strong oxidising and reducing agents, electroplating and other chemicals in aqueous solutions.

Not suitable for hydrocarbon type solvents such as Hexane, Naphtha, Petroleum, Ether, etc. Maximum service temperature: 80 °C. (60 °C for double and triple lengths).

CCS TYPE

Cotton media and matrix, 304 stainless steel core.

Proposed for general fluid applications. Temperature up to 120 °C - Dilute acids (1%).

Dilute alkalis (5%). For gases, the temperature must not exceed 100 °C.

Cotton can be bleached and washed to remove all wax and lubricants to permit acceptability on potable water, beverages and food products.

CCT TYPE

Cotton media and matrix, 316 stainless steel core.

Proposed for all general fluids at temperature rating up to 120 °C. For gases, temperature must not exceed 100 °C.

Same applications as for the CCS but greater chemical resistance of the core to acids and alkalis.

Special types

Other materials combinations can be produced on request with minimum order quantities, particularly the following types:

- D-PPS: polypropylene media and matrix, 304 SS core
- D-PPT: polypropylene media and matrix, 316 SS core
- D-CCP: cotton media and matrix, polypropylene core
- D-CCF: cotton media and matrix, tinned steel core.

Important Notice

3M Purification MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Since a variety of factors can affect the use and performance of a 3M Purification product in a particular application, some of which are uniquely within the user's knowledge and control, user is responsible for determining whether or not the 3M Purification product is fit for a particular purpose and suitable for user's method of application.

Limited Warranty

3M Purification warrants it this product to be free from defects in material and workmanship during normal use for a period of one (1) year from the date of shipment from the factory. If the Product(s) is (are) defective within this warranty period, your exclusive remedy and 3M Purification's sole obligations shall be, at 3M Purification's option, to replace or repair the Product(s) or refund the original purchase price of the Product(s). This warranty does not apply to failures that result from abuse, misuse, alteration or damage not caused by 3M Purification or failure to properly follow installation and use instructions.

Limitation of Liability: 3M Purification will not be liable for any loss or damage arising from the use of the Product(s), whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.

This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.



LENNTECH

info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289

Note: Micro-Klean D is new name of Micro-Wynd.

3M and Micro-Klean are trademarks of 3M used under licence.

For more contact addresses visit our website www.3M.eu/filtration or www.3Mpurification.com/international.

Data may be subject to change without further notice.

© 3M 2010. All rights reserved.

D-CCP21CB D-CCP21CB

DWTCZ01	DWTCZ02	DWTCZ03	DWTCZ04	DWTCZ05	DWTCZ06	DWTCZ07	DWTCZ08	DWTCZ09	DWTCZ10	DWTCZ11	DWTCZ12	DWTCZ13	DWTCZ14	DWTCZ15	DWTCZ16	DWTCZ17	DWTCZ18	DWTCZ19	DWTCZ20	DWTCZ21	DWTCZ22	DWTCZ23	DWTCZ24	DWTCZ25	DWTCZ26	DWTCZ27	DWTCZ28	DWTCZ29	DWTCZ30
DWTCZ31	DWTCZ32	DWTCZ33	DWTCZ34	DWTCZ35	DWTCZ36	DWTCZ37	DWTCZ38	DWTCZ39	DWTCZ40	DWTCZ41	DWTCZ42	DWTCZ43	DWTCZ44	DWTCZ45	DWTCZ46	DWTCZ47	DWTCZ48	DWTCZ49	DWTCZ50	DWTCZ51	DWTCZ52	DWTCZ53	DWTCZ54	DWTCZ55	DWTCZ56	DWTCZ57	DWTCZ58	DWTCZ59	DWTCZ60
DWTCZ61	DWTCZ62	DWTCZ63	DWTCZ64	DWTCZ65	DWTCZ66	DWTCZ67	DWTCZ68	DWTCZ69	DWTCZ70	DWTCZ71	DWTCZ72	DWTCZ73	DWTCZ74	DWTCZ75	DWTCZ76	DWTCZ77	DWTCZ78	DWTCZ79	DWTCZ80	DWTCZ81	DWTCZ82	DWTCZ83	DWTCZ84	DWTCZ85	DWTCZ86	DWTCZ87	DWTCZ88	DWTCZ89	DWTCZ90
DWTCZ91	DWTCZ92	DWTCZ93	DWTCZ94	DWTCZ95	DWTCZ96	DWTCZ97	DWTCZ98	DWTCZ99	DWTCZ100	DWTCZ101	DWTCZ102	DWTCZ103	DWTCZ104	DWTCZ105	DWTCZ106	DWTCZ107	DWTCZ108	DWTCZ109	DWTCZ110	DWTCZ111	DWTCZ112	DWTCZ113	DWTCZ114	DWTCZ115	DWTCZ116	DWTCZ117	DWTCZ118	DWTCZ119	DWTCZ120
DWTCZ121	DWTCZ122	DWTCZ123	DWTCZ124	DWTCZ125	DWTCZ126	DWTCZ127	DWTCZ128	DWTCZ129	DWTCZ130	DWTCZ131	DWTCZ132	DWTCZ133	DWTCZ134	DWTCZ135	DWTCZ136	DWTCZ137	DWTCZ138	DWTCZ139	DWTCZ140	DWTCZ141	DWTCZ142	DWTCZ143	DWTCZ144	DWTCZ145	DWTCZ146	DWTCZ147	DWTCZ148	DWTCZ149	DWTCZ150
DWTCZ151	DWTCZ152	DWTCZ153	DWTCZ154	DWTCZ155	DWTCZ156	DWTCZ157	DWTCZ158	DWTCZ159	DWTCZ160	DWTCZ161	DWTCZ162	DWTCZ163	DWTCZ164	DWTCZ165	DWTCZ166	DWTCZ167	DWTCZ168	DWTCZ169	DWTCZ170	DWTCZ171	DWTCZ172	DWTCZ173	DWTCZ174	DWTCZ175	DWTCZ176	DWTCZ177	DWTCZ178	DWTCZ179	DWTCZ180
DWTCZ181	DWTCZ182	DWTCZ183	DWTCZ184	DWTCZ185	DWTCZ186	DWTCZ187	DWTCZ188	DWTCZ189	DWTCZ190	DWTCZ191	DWTCZ192	DWTCZ193	DWTCZ194	DWTCZ195	DWTCZ196	DWTCZ197	DWTCZ198	DWTCZ199	DWTCZ200	DWTCZ201	DWTCZ202	DWTCZ203	DWTCZ204	DWTCZ205	DWTCZ206	DWTCZ207	DWTCZ208	DWTCZ209	DWTCZ210
DWTCZ211	DWTCZ212	DWTCZ213	DWTCZ214	DWTCZ215	DWTCZ216	DWTCZ217	DWTCZ218	DWTCZ219	DWTCZ220	DWTCZ221	DWTCZ222	DWTCZ223	DWTCZ224	DWTCZ225	DWTCZ226	DWTCZ227	DWTCZ228	DWTCZ229	DWTCZ230	DWTCZ231	DWTCZ232	DWTCZ233	DWTCZ234	DWTCZ235	DWTCZ236	DWTCZ237	DWTCZ238	DWTCZ239	DWTCZ240
DWTCZ241	DWTCZ242	DWTCZ243	DWTCZ244	DWTCZ245	DWTCZ246	DWTCZ247	DWTCZ248	DWTCZ249	DWTCZ250	DWTCZ251	DWTCZ252	DWTCZ253	DWTCZ254	DWTCZ255	DWTCZ256	DWTCZ257	DWTCZ258	DWTCZ259	DWTCZ260	DWTCZ261	DWTCZ262	DWTCZ263	DWTCZ264	DWTCZ265	DWTCZ266	DWTCZ267	DWTCZ268	DWTCZ269	DWTCZ270
DWTCZ271	DWTCZ272	DWTCZ273	DWTCZ274	DWTCZ275	DWTCZ276	DWTCZ277	DWTCZ278	DWTCZ279	DWTCZ280	DWTCZ281	DWTCZ282	DWTCZ283	DWTCZ284	DWTCZ285	DWTCZ286	DWTCZ287	DWTCZ288	DWTCZ289	DWTCZ290	DWTCZ291	DWTCZ292	DWTCZ293	DWTCZ294	DWTCZ295	DWTCZ296	DWTCZ297	DWTCZ298	DWTCZ299	DWTCZ300
DWTCZ301	DWTCZ302	DWTCZ303	DWTCZ304	DWTCZ305	DWTCZ306	DWTCZ307	DWTCZ308	DWTCZ309	DWTCZ310	DWTCZ311	DWTCZ312	DWTCZ313	DWTCZ314	DWTCZ315	DWTCZ316	DWTCZ317	DWTCZ318	DWTCZ319	DWTCZ320	DWTCZ321	DWTCZ322	DWTCZ323	DWTCZ324	DWTCZ325	DWTCZ326	DWTCZ327	DWTCZ328	DWTCZ329	DWTCZ330
DWTCZ331	DWTCZ332	DWTCZ333	DWTCZ334	DWTCZ335	DWTCZ336	DWTCZ337	DWTCZ338	DWTCZ339	DWTCZ340	DWTCZ341	DWTCZ342	DWTCZ343	DWTCZ344	DWTCZ345	DWTCZ346	DWTCZ347	DWTCZ348	DWTCZ349	DWTCZ350	DWTCZ351	DWTCZ352	DWTCZ353	DWTCZ354	DWTCZ355	DWTCZ356	DWTCZ357	DWTCZ358	DWTCZ359	DWTCZ360
DWTCZ361	DWTCZ362	DWTCZ363	DWTCZ364	DWTCZ365	DWTCZ366	DWTCZ367	DWTCZ368	DWTCZ369	DWTCZ370	DWTCZ371	DWTCZ372	DWTCZ373	DWTCZ374	DWTCZ375	DWTCZ376	DWTCZ37													