

NOCCHI QES PLUS

SINGLE PHASE ELECTRICAL PANEL FOR CONTROL OF AN ELECTRIC SUBMERSIBLE PUMP WITH DIRECT STARTING

MAIN COMPONENTS

- IP 55 plastic enclosure
- Main switch with disconnect device.
- Motor protector with reset button.
- Start-up capacitor
- Terminal board
- Cable clamp

TECHNICAL SPECIFICATIONS

- Protection rating: IP 55
- Power supply voltage: 230V/ 1F 50 Hz
- External dimensions 115 - 185 - 65 mm
- Weight: 0.6 kg

APPLICATION LIMITS


- Ambient temperature: -5 / +40 °C.
- Relative humidity: 50% at 40°C condensate free.
- Reference standards: EN 60335-1 - EN 60439-1.

OPERATION

- Manual via the main switch.
- Automatic via external remote control (pressure switch, float etc.)

OPTIONAL ACCESSORIES

- Floats or pressure switches (see relative table)



MODEL	Volt	Power		Field of application A	µF	Compatible el. pumps
		min kW	max kW			
QES PLUS 10/37 M	230 1F	0.37	0.55	4	16	SCM 4" PLUS SCM 4 HF 4" MOTORS
QES PLUS 10/55 M	230 1F	0.55	0.75	6	20	
QES PLUS 10/75 M	230 1F	0.75	1	7	30	
QES PLUS 10/75 M	230 1F	0.75	1	7	35	
QES PLUS 10/110 M	230 1F	1.1	1.5	9	40	
QES PLUS 10/150 M	230 1F	1.5	2	12	50	

