

PENTEK® FLAT CAP SLIM LINE® SERIES FILTER HOUSINGS

AN EXCELLENT CHOICE FOR LOW-FLOW APPLICATIONS & WHEN SPACE AND CHEMICAL COMPATIBILITY ARE PRIMARY CONCERNS



Pentair® Pentek® Flat Cap Slim Line® Filter Housings are manufactured of a durable polypropylene or clear Styrene-Acrylonitrile (SAN). These housings are available in 10" lengths, while the caps are available with 1/4" or 1/2" NPT connections.

Opaque Flat Cap Slim Line housings, molded from rugged reinforced polypropylene, offer outstanding chemical compatibility and are ideal for use in a variety of low-flow applications. These applications include undersink and countertop residential filtration, pre- and post-reverse osmosis filtration, recreational vehicle filtration, food service and humidifying systems.

Clear Flat Cap Slim Line housings offer on-site examination of flow, performance, and cartridge life. They are also ideal for a variety of applications.

FEATURES/BENEFITS

Slim design reduces space required for installation without sacrificing capacity

Available in 10" length

Available in clear or opaque sumps

Leak-proof seal

SPECIFICATIONS

Housing – Polypropylene (opaque) or Styrene Acrylonitrile (clear)

Cap – Reinforced Polypropylene

Button Assembly – 300 Series stainless steel, EPDM, and polypropylene

O-Ring – Buna-N®

Temperature Rating – 40-125°F (4.4-51.7°C)

Maximum Pressure – 125 psi (8.6 bar)



The 158739 is Tested and Certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements.

SPECIFICATIONS AND PERFORMANCE

PART #	DESCRIPTION	MAXIMUM DIMENSIONS	INITIAL ΔP (PSI) @ FLOW RATE (GPM)
158739*	1/4" #10 Flat Cap Slim Line® White/White w/o PR	12.36" x 4.63" (314 x 118 mm)	1 psi @ 10 gpm (0.07 bar @ 38 Lpm)
158784	1/4" #10 Flat Cap Slim Line White/Clear w/o PR	12.36" x 4.63" (314 x 118 mm)	1 psi @ 10 gpm (0.07 bar @ 38 Lpm)
158785	1/2" #10 Flat Cap Slim Line White/White w/o PR	12.36" x 4.63" (314 x 118 mm)	1 psi @ 10 gpm (0.07 bar @ 38 Lpm)
158786	1/2" #10 Flat Cap Slim Line Black/White w/o PR	12.36" x 4.63" (314 x 118 mm)	1 psi @ 10 gpm (0.07 bar @ 38 Lpm)

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage.

*WQA certified

ACCESSORIES

PART #	DESCRIPTION
150539	SW-1A for Slim Line
158095	Viton® #237 for Slim Line
158096	Silicone #237 for Slim Line
244047	SL-ZP Kit - Zinc Plated Bracket for Slim Line
357638	SL-SS - Stainless Steel Bracket ONLY for Slim Line
357644	SL-SS Kit - Stainless Steel Bracket for Slim Line
244046-00	SL-ZP - Zinc Plated Bracket ONLY for Slim Line
244627-02	Two-Housing System Bracket



LENNTECH

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

310927 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.