

AUTOTROL® 360 VALVE MANUAL FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS



FEATURES/BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Continuous service flow rate of 21 GPM with a backwash of 19 GPM

Backwash capability accommodates filter up to 36" in diameter

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Designed for single tank systems only

No programming required- fixed cycle times

User-initiated regeneration knob

External drain line flow control

OPTIONS

Filter only control valve

Plumbing connections in .75"-1.25" NPT and BSP

VALVE SPECIFICATIONS

Valve Body	Glass-filled Noryl®
Valve Color	Grey
Operating Pressure	20-125 PSI (1.38-8.61 BAR)
Water Temperature	35-100°F (2-38°C)
Ambient Temperature	35-122°F (2-50°C)
Cycle Steps	Service, backwash, fast rinse
Service Capabilities	Removable cam, flapper access
Cam Position Indicator	Knob

VALVE CONNECTIONS

Tank Thread	2.5"
Inlet/Outlet	1" NPT or 1" BSP
Inlet/Outlet (center to center)	4"
Drain Location	0.75" below inlet/outlet

DIMENSIONS

Width	8.6"
Height	3.35"
Riser Tube Dia.	1.05"
Riser Height	Flush +/- 0.5"

PERFORMANCE

Drain Line Flow Control	4-20 gpm
Full Flow Body	Service: 21 gpm Backwash: 19 gpm Fast Rinse: 5 gpm



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289