



- Energy saving thanks to high efficiency hydraulic performances and Inverter device for constant pressure control
- Self-priming pump with 2l tank
- Auto-Diagnosis
- Dry running and motor overheating protection

Model: **EVOTRONIC 350**
 Part number: **N4501330**
 Barcode: **7630014581177**

EVOTRONIC 350 is a system composed of a multistage self-priming pump with stainless steel pump body and an electronic frequency changer (inverter) that, according to the effective water demand, allows the pressure to be maintained constant in the system, by reducing or increasing the electric pump motor rotation speed.


LENNTECH
WATER TREATMENT SOLUTIONS

info@lenntech.com Tel. +31-152-610-900
 www.lenntech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	1100 W	POWER CABLE	1.5 m
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	33.25 mm (1" F)
FLOW RATE	5600 l/h	MAX. ADVISED SUCTION HEAD	8 m
MAX. HEAD	57 m	WEIGHT	13.3 kg
RATED CURRENT	7 A	PACKAGING DIMENSIONS	30 cm x 42 cm 35 cm h
N° IMPELLERS	4	ACCESSORIES	-
PROTECTION CLASS	IPX5		
PUMP BODY	Stainless Steel		x 4