



- Aluminium die-casting and stainless steel pump body
- Dry running protection by float switch
- Ergonomic handle

Model: **SUB 3 S**
 Part number: **N3016120**
 Barcode: **8010583124347**

Submersible pump with asynchronous single phase motor with built-in thermal relay and stainless steel motor shaft. SUB 3S is equipped with float switch for automatic working and dry running protection.


LENNTECH
WATER TREATMENT Solutions

info@lenntech.com Tel. +31-152-610-900
 www.lenntech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	800 W	POWER CABLE	10 m H07 RN8-F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1 1/4")
FLOW RATE	6000 l/h	MAX. WATER TEMPERATURE	40°C
MAX. HEAD	30 m	WEIGHT	7.4 kg
RATED CURRENT	4 A	PACKAGING DIMENSIONS	21.5 x 17 x 35.5 cm
N° IMPELLERS	3	PCS PER PALLET	48
MIN. OPERATING SPACE	500 mm	ACCESSORIES	-
MAX. IMMERSION DEPTH	7 m		x 2