



- Double mechanical seal for great reliability, reduction of maintenance operations and continuous duty.
- Very high flow and pressure
- Stainless steel pump body
- Stainless steel motor shaft
- Integrated check valve
- For very deep wells

Model: **SUB 6000/75 Plus**
 Part number: **N32000240**
 Barcode: **7630014535323**

Submersible pump with asynchronous single phase motor, stainless steel pump body and motor shaft. SUB 6000/75 Plus is ideal for pumping water from very deep wells or from wells that are located far away from water sources, thanks to the high pressure performances.


LENNTECH
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
 www.lennotech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	1300 W	POWER CABLE	30 m H07 RN8-F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1 1/4")
FLOW RATE	6000 l/h	MAX.WATER TEMPERATURE	40°C
PRESSURE/MAX.HEAD	71 m / 7.1 bar	WEIGHT	12.5 Kg
RATED CURRENT	6 A	PACKAGING DIMENSIONS	80 x 22.5 x 10.5 cm
N° IMPELLERS	10	PCS PER PALLET	30
MIN.OPERATING SPACE	100 mm	ACCESSORIES	-
MAX.IMMERSION DEPTH	27 m		x 7