



- Stainless steel pump body and motor shaft
- Double mechanical seal for great reliability, reduction of maintenance operations and continuous duty.
- Integrated check valve
- 20 m safety rope

Model: **SUB 8 S PLUS
AUTO**
 Part number: **N3200200-P**
 Barcode: **7630014535286**

Submersible pump with asynchronous single phase motor, stainless steel pump body and motor shaft. SUB 8S Plus AUTO has a mechanical seal in graphite and reinforcement in ceramic, built-in condenser and integrated check valve. Dry running protection thanks to PRESSUREMATE device.


LENNTECH
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
 www.lennotech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	1100 W	POWER CABLE	22 m H07 RN-8F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1 1/4")
FLOW RATE	6000 l/h	MAX. WATER TEMPERATURE	40°C
PRESSURE/MAX. HEAD	57 m	WEIGHT	13.2 kg
RATED CURRENT	5 A	PACKAGING DIMENSIONS	75 x 33 x 12 cm
N° IMPELLERS	8	PCS PER PALLET	20
MIN. OPERATING SPACE	100 mm	ACCESSORIES	-
MAX. IMMERSION DEPTH	19 m		x 5