



- Stainless steel pump body and motor shaft
- Double mechanical seal for great reliability, reduction of maintenance operations and continuous duty
- Integrated check valve
- 20 m safety rope

Model: **SUB 8 S PLUS**
 Part number: **N3200200**
 Barcode: **7630014536023**

Submersible pump with asynchronous single phase motor, stainless steel pump body and stainless steel motor shaft. SUB 8S Plus has a double mechanical seal increasing the shaft resistance to stress due to the pump working.


LENNTECH
WATER TREATMENT SOLUTIONS

info@lenntech.com Tel. +31-152-610-900
 www.lenntech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	1100 W	POWER CABLE	22 m H07 RN8-F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1 1/4")
FLOW RATE	6000 l/h	MAX. WATER TEMPERATURE	40°C
PRESSURE/MAX. HEAD	57 m	WEIGHT	10.6 kg
RATED CURRENT	5 A	PACKAGING DIMENSIONS	74 x 19 x 16 cm
N° IMPELLERS	8	PCS PER PALLET	30
MIN. OPERATING SPACE	100 mm	ACCESSORIES	-
MAX. IMMERSION DEPTH	19 m		x 5