



TECHNICAL SHEET

PENTAIR

RO-2600 5 STAGE RO SYSTEM
WITH PUMP



LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289



PENTAIR RO-2600 5 STAGE RO SYSTEM WITH PUMP



TECHNICAL CHARACTERISTICS

- Thin Layer Composite membrane: TLC-75
- Pressure range: 1.4–6.9 bar
- Temperature range: 4.4–37.7°C
- Total dissolved solids: 2000 ppm
- Maximum hardness*: 171 mg/L
- Sulfide, iron and manganese**: <0.1 ppm
- Chlorine in water supply: <2 ppm
- pH limits: 3–11
- Daily product water rate***: 227 Lpd
- TDS rejection: 90% @ 2 bar inlet
- Turbidity: 5 NTU Max

SPECIFICATIONS

Overall dimensions	45.7 x 20.3 x 45.7 cm
Tank dimensions	34.3 x 27.9 cm
Weight	10.4 kg
Tank capacity max	16.5 L
Tank air pressure empty	0.34–0.48 bar
Tank weight full	12.9 kg

* If the hardness of your water is above 171 mg/L, lime scale will build up rapidly on the membrane inside of the RO membrane cartridge. Scale build-up will clog the RO membrane cartridge and make the system ineffective. We do not recommend the reverse osmosis system to be used with water in excess of 171 mg/L hardness.

**A maximum total level of approximately 0.1 ppm sulfide, iron or manganese is permissible. See your local dealer to reduce these substances in your water

***Based on manufacturer's internal testing.



RO-2600 COMPONENTS



SYSTEM CONSUMABLES

- Sediment cartridge P5
- Carbon block cartridge EPM 10
- Granular activated carbon cartridge GAC 10
- Inline cartridge GS-10 RO
- RO membrane TLC-75

For technical specifications of these components please refer to the technical sheet of 5 stage RO Bundle kit. System consumables can also be purchased all together under the part number **ROKIT5000**.

HRO BOOSTER PUMP



TECHNICAL CHARACTERISTICS

- Model: 8015-014-011
- Capacity: 380 Lpd
- Voltage: 24 Vdc
- Amps: 2.2
- Ports: 3/8 inch NPT-F
- Bypass: 5.5 bar
- Pump design: positive displacement diaphragm pump
- Motor: 24 Vdc permanent magnet motor, CE listed

PERFORMANCE*

1.4 bar	181 Lph
2.8 bar	166 Lph
4.1 bar	151 Lph
5.5 bar	113 Lph
6.9 bar	41 Lph

* 1.4 bar Inlet pressure

Contact us:

LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289