

Data Sheet

LENNTECH

info@lennotech.com

www.lennotech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

Polygard®-CN Filters

Versatile pleated filters for the clarification and prefiltration of process fluids

Polygard®-CN products are nominally rated filters designed for particle removal applications in liquids and gases. The pleated structure of Polygard®-CN filter media minimizes pressure differentials during the filtration process, and the all-polypropylene construction of these filters conveys low levels of extractables and broad chemical compatibility. Downstream filter performance is enhanced due to efficient particle and microorganism reduction.

Benefits

- Nominal particle retention rating
- Low pressure drop
- Low extractables levels
- Broad range of micron ratings to match an array of particle removal applications
- Designed for rigorous process conditions and broad chemical compatibility
- Ideal for designing scalable solutions from bench top to full-scale manufacturing



Regulatory Compliance

Polygard®-CN filters are designed, developed, and manufactured in accordance with a Quality Management System approved by an accredited registering body to an ISO® 9000 Quality Systems Standard and are shipped with a Certificate of Quality. Each Opticap® XL capsule and cartridge filter is supported by a Validation Guide for compliance with regulatory requirements. For traceability and easy identification, each filter is marked with identifying characteristics.

Multiple Formats Available

Polygard®-CN filters are available in three formats, seven pore sizes, and multiple configurations that vary by filtration area and the type of inlet/outlet connection.

Media Types

Polygard®-CN (nominal)

- 0.3 µm
- 0.6 µm
- 1.2 µm
- 2.5 µm
- 5.0 µm
- 10.0 µm
- 30.0 µm

Filter Formats

- OptiScale® small-scale disposable capsule filters
- Opticap® XL disposable capsule filters
- Cartridge filters



OptiScale® Process Development Screening Tool

OptiScale® disposable capsule filters with Polygard®-CN media provide a convenient small-volume option for process screening and scaling. These "drop in" filters are ideal for evaluating biopharmaceuticals. OptiScale® capsule filters offer speed-to-market strategies for efficiently developing compounds and biotherapeutics.

The OptiScale® disposable capsule is ideally suited for process development and screening. OptiScale® capsules are faster and easier to set up than conventional 47 mm discs.



OptiScale® Filters

Opticap® XL Disposable Capsule Filters

Opticap® XL disposable capsule filters with Polygard®-CN media are available in two filter sizes.

The patented Opticap® XL capsule design allows unparalleled thermal and hydraulic stress resistance in a disposable filter, resulting in reliability, high confidence in the sterility process and improved cleanliness. The unique capsule design with pleated Polygard®-CN media minimizes hold-up volume and reduces production losses.

Convenient and Easy to Use

Opticap® XL capsule filters eliminate the time and the expense associated with assembling, cleaning, and validating stainless steel housings. Adjustable, easy-to-turn, upstream vents and drain valves with o-ring seals and hose barb connections allow for easy process control. Other ease-of-use features include flow directional arrows and ribbed edges for easy gripping even with gloved hands.



Opticap® XL Filters

The Right Size

A range of filter sizes is available to fit all of your application needs, and to allow easy scale-up of your small volume filtration steps to larger, full-scale filtration processes.

The Right Connections

Self-contained and disposable, Opticap® XL capsule filters are supplied with a choice of inlet and outlet connections to optimize your filtration process, including sanitary flanges which enables a higher flow rate, fractional sanitary flanges, and hose barbs.

Cartridge Filters

Polygard®-CN cartridge filters provide high throughput and minimal differential pressure. Cartridges are robust, strong, resilient and are designed to withstand multiple steam-in-place cycles.

A full range of filter sizes is available to suit your application requirements. A variety of connection options are offered for easy adaptation to existing housings.



Cartridge Filters

Specifications


OptiScale®			
Nominal Dimensions			
Inlet/outlet:	Flange/hose barb	Flange/flange	Hose barb/hose barb
Maximum length:	82 mm (3.24 in.)	74 mm (2.91 in.)	94 mm (3.70 in.)
Diameter:	69 mm (2.75 in.)	69 mm (2.75 in.)	69 mm (2.75 in.)
Weight:	2.3 oz (67 g)	2.3 oz (67 g)	2.3 oz (67 g)
Filtration Area	13.8 cm²		
Materials of Construction			
Filter media:	Polypropylene		
Structural components:	Polycarbonate		
Vent cap:	PVDF		
Internal seal rings:	fluoroelastomers		
Housing Vent	Adjustable vent with male luer and female Luer-Lok™ connections on inlet side of device.		
Maximum Inlet Pressure	5.5 bar (80 psi) at 25 °C		
Oxidizable Substances	Capsules meet the requirements of the USP Oxidizable Substance for Sterile Water for Filtration Test after a water flush of ≤ 100 mL.		
Sterilization by Autoclave	May be autoclaved for 3 cycles of 60 minutes at 126 °C.		
Good Manufacturing Practices	These products are manufactured in a facility which adheres to FDA Good Manufacturing Practices.		
Component Material Toxicity	Component materials were tested and meet the criteria of the USP <88> Reactivity Test for Class VI Plastics. This product is non-toxic per the USP <88> Safety Test.		
Indirect Food Additive	All component materials meet the FDA Indirect Food Additive requirements cited in 21 CFR 177-182.		

Specifications (continued)


	Opticap® XL 5	Opticap® XL 10	Cartridge Filters 4-inch	Per 10-inch
Nominal Dimensions				
Maximum length:	21.6 cm (8.5 in.)	33.5 cm (13.2 in.)	—	—
Diameter:	10.7 cm (4.2 in.)	10.7 cm (4.2 in.)	71 mm (2.75 in.)	70 mm (2.75 in.)
Filtration Area	0.18 m² (1.9 ft²)	0.42 m² (4.5 ft²)	0.18 m² (1.9 ft²)	0.42 m² (4.5 ft²)
Materials of Construction				
Filter media:	Polypropylene		Polypropylene	
Supports:	Polypropylene		Polypropylene	
Structural components:	Polypropylene		Polypropylene	
Vent o-rings:	Silicone		—	
O-rings:	—		Ethylene Propylene (Std)	
Vent/Drain	¼ in. hose barb with double o-ring seal		—	
Maximum Inlet Pressure	5.5 bar (80 psi) at 25 °C 2.8 bar (40 psi) at 60 °C 1.0 bar (15 psi) at 80 °C		— — —	
Maximum Operating Temperature	—		80 °C continuous	
Maximum Differential Pressure				
Forward:	4.8 bar (70 psid) at 20 °C			
NVR Gravimetric Extractables	After autoclaving and a 24 hour soak in ASTM® Type 1 reagent grade water at controlled room temperature:			
	≤25 mg	≤55 mg	—	≤50 mg
Bacterial Endotoxin	Aqueous extraction contains <0.5 EU/mL as determined by the Limulus Amebocyte Lysate (LAL) Test.			
Oxidizable Substances	Capsules meet the requirements of the USP Oxidizable Substances Test after a water flush of:			
	≤2000 mL	≤5000 mL	—	5000 mL
Sterilization by Autoclave	May be autoclaved for 3 cycles of 30 minutes at 126 °C. (Cannot be steam sterilized in-line)		May be autoclaved for 10 cycles of 30 minutes at 126 °C or steam sterilized for 10 cycles for 30 minutes at 126 °C or hot water sanitized at 80 °C maximum for 30 minutes.	
Component Material Toxicity	Component materials were tested and meet the criteria of the USP <88> Reactivity Test for Class VI Plastics. Polygard®-CN filters meet the requirements of the USP <88> Safety Test utilizing a 0.9% sodium chloride extraction.			
Indirect Food Additive	All component materials meet the FDA Indirect Food Additive requirements cited in 21 CFR 177-182.			
European Pressure Equipment Directive	We certify that this product complies with the European Pressure Equipment Directive, 97/23/EC of 29 May 1997. This product has been classified under Article 3 § 3 of the Pressure Vessel Directive. It has been designed and manufactured in accordance with sound engineering practice to ensure safe use. In compliance with Article 3 § 3 of this Pressure Equipment Directive, this product does not bear the CE mark.		—	—

Typical Clean Water Flow Rates


Opticap® XL 5 Capsule with Polygard®-CN Media — 0.3 µm Nominal (KN03)




Opticap® XL 5 Capsule with Polygard®-CN Media — 5.0 µm Nominal (KN50)



Opticap® XL 10 Capsule with Polygard®-CN Media — 0.3 µm Nominal (KN03)



Opticap® XL 10 Capsule with Polygard®-CN Media — 5.0 µm Nominal (KN50)



Opticap® XL Legends Refer to Connection Type

TT = 38 mm (1½ in.)
Sanitary Flange Inlet
and Outlet


FF = 19 mm (¾ in.)
Sanitary Flange Inlet
and Outlet

HH = 14 mm (⅝ in.) Hose
Barb Inlet and Outlet

Cartridge Legend Refers to Pore Size


CN03 = 0.3 µm
CN06 = 0.6 µm
CN12 = 1.2 µm
CN25 = 2.5 µm
CN50 = 5.0 µm

Cartridge Filter with Polygard®-CN Media — 10-inch




Ordering Information

OptiScale® Capsule Filters




Opticap® XL Capsule Filters



Ordering Information

Cartridge Filters



To Place an Order or Receive Technical Assistance

LENNTECH bv

Rotterdamseweg 402m

2629HH Delft

The Netherlands

info@lennotech.com

www.lennotech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89



Polygard-CN-Filters

SN03A47HH3	CN0301E06	CN1201E06	CN5001E06	CN3H01E06
SN03A47FF3	CN0301V06	CN1201V06	CN5001V06	CN3H01V06
SN03A47FH3	CN0301S06	CN1201S06	CN5001S06	CN3H01S06
SN06A47HH3	CN0301T06	CN1201T06	CN5001T06	CN3H01T06
SN06A47FF3	CN0302E06	CN1202E06	CN5002E06	CN3H02E06
SN06A47FH3	CN0302V06	CN1202V06	CN5002V06	CN3H02V06
SN12A47HH3	CN0302S06	CN1202S06	CN5002S06	CN3H02S06
SN12A47FF3	CN0302T06	CN1202T06	CN5002T06	CN3H02T06
SN12A47FH3	CN0303E06	CN1203E06	CN5003E06	CN3H03E06
SN25A47HH3	CN0303V06	CN1203V06	CN5003V06	CN3H03V06
SN25A47FF3	CN0303S06	CN1203S06	CN5003S06	CN3H03S06
SN25A47FH3	CN0303T06	CN1203T06	CN5003T06	CN3H03T06
SN50A47HH3	CN0351E06	CN1251E06	CN5051E06	CN3H51E06
SN50A47FF3	CN0351V06	CN1251V06	CN5051V06	CN3H51V06
SN50A47FH3	CN0351S06	CN1251S06	CN5051S06	CN3H51S06
SN1HA47HH3	CN0351T06	CN1251T06	CN5051T06	CN3H51T06
SN1HA47FF3	CN0352E06	CN1252E06	CN5052E06	CN3H52E06
SN1HA47FH3	CN0352V06	CN1252V06	CN5052V06	CN3H52V06
SN3HA47HH3	CN0352S06	CN1252S06	CN5052S06	CN3H52S06
SN3HA47FF3	CN0352T06	CN1252T06	CN5052T06	CN3H52T06
SN3HA47FH3	CN0353E06	CN1253E06	CN5053E06	CN3H53E06
KN03A05TT1	CN0353V06	CN1253V06	CN5053V06	CN3H53V06
	CN0353S06	CN1253S06	CN5053S06	CN3H53S06
KN03A05FF1	CN0353T06	CN1253T06	CN5053T06	CN3H53T06
KN03A05HH1	CN0371E06	CN1271E06	CN5071E06	CN3H71E06
KN03A10TT1	CN0371V06	CN1271V06	CN5071V06	CN3H71V06
KN03A10FF1	CN0371S06	CN1271S06	CN5071S06	CN3H71S06
KN03A10HH1	CN0371T06	CN1271T06	CN5071T06	CN3H71T06
KN06A05TT1	CN0372E06	CN1272E06	CN5072E06	CN3H72E06
KN06A05FF1	CN0372V06	CN1272V06	CN5072V06	CN3H72V06
KN06A05HH1	CN0372S06	CN1272S06	CN5072S06	CN3H72S06
KN06A10TT1	CN0372T06	CN1272T06	CN5072T06	CN3H72T06
KN06A10FF1	CN0373E06	CN1273E06	CN5073E06	CN3H73E06
KN06A10HH1	CN0373V06	CN1273V06	CN5073V06	CN3H73V06
KN12A05TT1	CN0373S06	CN1273S06	CN5073S06	CN3H73S06
KN12A05FF1	CN0373T06	CN1273T06	CN5073T06	CN3H73T06
KN12A05HH1	CN03F1E06	CN12F1E06	CN50F1E06	CN3HF1E06
KN12A10TT1	CN03F1V06	CN12F1V06	CN50F1V06	CN3HF1V06
KN12A10FF1	CN03F1S06	CN12F1S06	CN50F1S06	CN3HF1S06
KN12A10HH1	CN03F1T06	CN12F1T06	CN50F1T06	CN3HF1T06
KN25A05TT1	CN03F2E06	CN12F2E06	CN50F2E06	CN3HF2E06
KN25A05FF1	CN03F2V06	CN12F2V06	CN50F2V06	CN3HF2V06
KN25A05HH1	CN03F2S06	CN12F2S06	CN50F2S06	CN3HF2S06
KN25A10TT1	CN03F2T06	CN12F2T06	CN50F2T06	CN3HF2T06
KN25A10FF1	CN03F3E06	CN12F3E06	CN50F3E06	CN3HF3E06
KN25A10HH1	CN03F3V06	CN12F3V06	CN50F3V06	CN3HF3V06
KN50A05TT1	CN03F3S06	CN12F3S06	CN50F3S06	CN3HF3S06
KN50A05FF1	CN03F3T06	CN12F3T06	CN50F3T06	CN3HF3T06
KN50A05HH1	CN0601E06	CN2501E06	CN1H01E06	CN03M4E06
KN50A10TT1	CN0601V06	CN2501V06	CN1H01V06	
KN50A10FF1	CN0601S06	CN2501S06	CN1H01S06	CN03M4V06
KN50A10HH1	CN0601T06	CN2501T06	CN1H01T06	CN03M4S06
KN1HA05TT1	CN0602E06	CN2502E06	CN1H02E06	CN03M4T06
KN1HA05FF1	CN0602V06	CN2502V06	CN1H02V06	CN06M4E06
KN1HA05HH1	CN0602S06	CN2502S06	CN1H02S06	CN06M4V06
KN1HA10TT1	CN0602T06	CN2502T06	CN1H02T06	CN06M4S06
KN1HA10FF1	CN0603E06	CN2503E06	CN1H03E06	CN06M4T06
KN1HA10HH1	CN0603V06	CN2503V06	CN1H03V06	CN12M4E06
KN3HA05TT1	CN0603S06	CN2503S06	CN1H03S06	CN12M4V06
KN3HA05FF1	CN0603T06	CN2503T06	CN1H03T06	CN12M4S06
KN3HA05HH1	CN0651E06	CN2551E06	CN1H51E06	CN12M4T06
KN3HA10TT1	CN0651V06	CN2551V06	CN1H51V06	CN25M4E06
KN3HA10FF1	CN0651S06	CN2551S06	CN1H51S06	CN25M4V06
KN3HA10HH1	CN0651T06	CN2551T06	CN1H51T06	CN25M4S06
	CN0652E06	CN2552E06	CN1H52E06	CN25M4T06
	CN0652V06	CN2552V06	CN1H52V06	CN50M4E06
	CN0652S06	CN2552S06	CN1H52S06	CN50M4V06
	CN0652T06	CN2552T06	CN1H52T06	CN50M4S06
	CN0653E06	CN2553E06	CN1H53E06	CN50M4T06
	CN0653V06	CN2553V06	CN1H53V06	CN1HM4E06
	CN0653S06	CN2553S06	CN1H53S06	CN1HM4V06
	CN0653T06	CN2553T06	CN1H53T06	CN1HM4S06
	CN0671E06	CN2571E06	CN1H71E06	CN1HM4T06
	CN0671V06	CN2571V06	CN1H71V06	CN3HM4E06
	CN0671S06	CN2571S06	CN1H71S06	CN3HM4V06
	CN0671T06	CN2571T06	CN1H71T06	CN3HM4S06
	CN0672E06	CN2572E06	CN1H72E06	CN3HM4T06
	CN0672V06	CN2572V06	CN1H72V06	
	CN0672S06	CN2572S06	CN1H72S06	
	CN0672T06	CN2572T06	CN1H72T06	
	CN0673E06	CN2573E06	CN1H73E06	
	CN0673V06	CN2573V06	CN1H73V06	
	CN0673S06	CN2573S06	CN1H73S06	
	CN0673T06	CN2573T06	CN1H73T06	
	CN06F1E06	CN25F1E06	CN1HF1E06	
	CN06F1V06	CN25F1V06	CN1HF1V06	
	CN06F1S06	CN25F1S06	CN1HF1S06	
	CN06F1T06	CN25F1T06	CN1HF1T06	
	CN06F2E06	CN25F2E06	CN1HF2E06	
	CN06F2V06	CN25F2V06	CN1HF2V06	
	CN06F2S06	CN25F2S06	CN1HF2S06	
	CN06F2T06	CN25F2T06	CN1HF2T06	
	CN06F3E06	CN25F3E06	CN1HF3E06	
	CN06F3V06	CN25F3V06	CN1HF3V06	
	CN06F3S06	CN25F3S06	CN1HF3S06	
	CN06F3T06	CN25F3T06	CN1HF3T06	