



Design Pressure = 300 PSI @ 120 °F
Min. Design Temperature = 20 °F @ 300 PSI
Hydrotest Pressure = 330 PSI

300 PSI
MEGA
SIDE PORT




info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289

NOTES:
DIMENSIONS IN INCHES (MM APPROX.)

FOR REFERENCE ONLY, NOT FOR CONSTRUCTION UNLESS CERTIFIED

SHIMMING OF THE SADDLES MAY BE REQUIRED

CENTER VESSEL ON 2 OR 3 SUPPORTS AT SPAN(S) "S".

INCORRECT MANIFOLDING WILL CAUSE SEVERE LOCAL STRESS AROUND PORT AND MAY RESULT IN LEAKS AND PREMATURE FAILURE. TAKE EVERY PRECAUTION LISTED IN THE ENGINEERING PACKET OR USERS MANUAL.

INTERNAL PERMEATE PRESSURE MUST NOT EXCEED 125 PSI.

ASME SECTION X, 2013
RP CODE STAMP OPTIONAL

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE


Vista, California, U.S.A.
www.protec-arisawa.com

PRO 8-300-MSP				
APPROVED AP 5/26/04	ECO 20002	REVISED 3/31/14	DRAWING 101021	REV T

*P1 Not Available With 4" Mega Side Port

Shell Length Code	L inch (mm)	P3 Standard inch (mm)	*P1 Optional inch (mm)	S Span in (mm)	Empty Weight lb (kg)
-1	58.4 [1483.36]	46 [1168.40]	47 [1193.80]	1 @ 28 [711.20]	63 [29]
-1.5	78.4 [1991.36]	66 [1676.40]	67 [1701.80]	1 @ 42 [1066.80]	73 [33]
-2	98.4 [2499.36]	86 [2184.40]	87 [2209.80]	1 @ 56 [1422.40]	83 [38]
-3	138.4 [3515.36]	126 [3200.40]	127 [3225.80]	1 @ 80 [2032.00]	103 [47]
-4	178.4 [4531.36]	166 [4216.40]	167 [4241.80]	2 @ 64 [1625.60]	123 [56]
-5	218.4 [5547.36]	206 [5232.40]	207 [5257.80]	2 @ 78 [1981.20]	143 [65]
-6	258.4 [6563.36]	246 [6248.40]	247 [6273.80]	2 @ 92 [2336.80]	163 [74]
-7	298.4 [7579.36]	286 [7264.40]	287 [7289.80]	2 @ 106 [2692.40]	183 [83]
-7.5	318.4 [8087.36]	306 [7772.40]	307 [7797.80]	2 @ 114 [2895.60]	193 [88]
-8	338.4 [8595.36]	326 [8280.40]	327 [8305.80]	2 @ 120 [3048.00]	203 [92]

NOTE: STANDARD PARTS ARE SHOWN FOR REFERENCE ONLY
CHECK ORIGINAL ORDER FOR ORDERING SPARE PARTS

ITEM	QTY	P/N	DESCRIPTION	MATERIAL
1	1	4080196	Shell	Filament Wound, Epoxy FRP
2	2	4080028	Bearing Plate	6061-T6 Aluminum, SB-221, Anodized
3	2	4080177-3	Sealing Plate	Noryl GFN2
4	2	4080254-1	Feed/Concentrate Port, 3", "K"	Stainless Steel, 316, SA-312
5	4	6201343	Retaining Ring, F/C Port, 3", "K"	Stainless Steel, 316, SA-479
6	2	6188504-N	O-Ring Seal, F/C Port, 3", "K"	Ethylene Propylene
7	2	4080309	Permeate Port	Noryl GFN2
8	2	6100442MK	Head Seal	Ethylene Propylene
9	2	6110229-N	Permeate Port Seal	Ethylene Propylene
10	2	4080320	Retaining Ring w/ Finger Pull	Stainless Steel, 316, SA-479
11	2	6121200	Retaining Ring, Permeate Port	Stainless Steel, 316
12	2*	4080173	Support Saddle	Thermoplastic Rubber
13	2	4080137	Strap Assembly	Stainless Steel, 316L
14	4	6150001	Strap Screw	Stainless Steel, 18-8
15	2	A/R	Adapter	Thermoplastic
16	1	4080165-1	Thrust Cone	PVC Thermoplastic
17	2	6110326-N	Adapter Seal	Ethylene Propylene
18	A/R	A/R	PWT Seal	Ethylene Propylene
19	3	4080062-4	Shim, Adapter	Noryl GFN2

*3 each with shell lengths -4 and longer.