

TECHNICAL SHEET

SIATA
SFE-EV PRO
CONTROLLER





SIATA SFE-EV PRO CONTROLLER



TECHNICAL CHARACTERISTICS

- Can be used on all SIATA valves for softening or filter applications, both in simplex or duplex mode
- Easy and simple, user-friendly programming
- Coloured LCD display:
 - High customization possibilities: customer logo, service phone number and password
 - Time of day alternating with volume remaining during the service
 - Salt status indicator
 - Indication of day of the week and time of the day in hours and minutes
 - Regeneration steps and cycle time remaining
- Easy and simple, user-friendly programming:
 - Different volume units set (liters, cubic meters or gallons)
 - Quick and easy setup of capacity, regeneration time, day override
 - Advanced programming options including up to 9 regenerations phases with independently adjustable cycle times
 - Cam on demand for customized applications
- 3 free contact relays, each one programmable in 8 different modes (for solenoid valve, dosing pump, ...)
- Modular functionality in duplex mode for higher volume demand
- Manual regeneration, meter immediate or delayed, time clock, day of week regeneration
- High frequency regeneration (every 2/3/4/6/8 or 12 hours)
- Remote start, immediate or delayed, inhibit
- Statistic Modes
- Programming is stored in the EEPROM and will not be lost due to power outages
- Interchangeable standard lithium battery (#CR2032)

LENNTECH
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

contact: techsupport.water@pentair.com