

DAB Pump 3 NKV AD 10-15

SETS WITH ACTIVE DRIVER 3-6-10 AT CONSTANT PRESSURE

LENNTECH

info@lennotech.com

www.lennotech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

Applications

Booster sets specifically suitable for civil or industrial use, irrigation systems and washing installations. These units are acclaimed for their supreme reliability, simplicity of operation and minimal maintenance requirements.

Construction features - components

- 3 NKV 10-15 type multistage vertical centrifugal electric pumps
- Skid in galvanized sheet steel
- Suction and discharge manifolds in galvanized steel (stainless steel on request)
- Ball valves with union on suction and discharge ports of each pump

- Check valves on discharge ports of each pump

- 2 plugs or blank flanges in galvanized steel for closing manifolds
- Radial pressure gauge with isolator valve
- 1 8 litre membrane pressure tank

Electrical section

- 1 Active Driver module on the discharge line of each pump (see Active Driver information at the beginning of this heading)
- 1 protection control unit"



TECHNICAL DATA - 3 NKV AD

MODEL	CODE	ELECTRICAL DATA			HYDRAULIC DATA		Ø		WEIGHT Kg
		VOLTAGE 50 Hz	P2 NOMINAL		Q m³/h	H m			
			kW X 3	HP X 3			A	M	
3NKV A.D. 10/5 T	60120102	3 X 400 V ~	2,2	3	4-24	50-30	DN 80	DN 80	412
3NKV A.D. 10/6 T	60120103	3 X 400 V ~	2,2	3	4-24	60 -30	DN 80	DN 80	415
3NKV A.D. 10/7 T	60120104	3 X 400 V ~	3	4	4-24	70-40	DN 80	DN 80	445
3NKV A.D. 10/8 T	60120105	3 X 400 V ~	3	4	4-24	80-50	DN 80	DN 80	448
3NKV A.D. 10/9 T	60120106	3 X 400 V ~	3	4	4-24	90-50	DN 80	DN 80	452
3NKV A.D. 10/10 T	60120107	3 X 400 V ~	4	5,5	4-24	100-60	DN 80	DN 80	481
3NKV A.D. 10/12 T	60120108	3 X 400 V ~	4	5,5	4-24	120-70	DN 80	DN 80	485
3NKV A.D. 10/14 T	60120109	3 X 400 V ~	5,5	7,5	4-24	140 - 80	DN 80	DN 80	571
3NKV A.D. 15/3 T	60120110	3 X 400 V ~	3	4	8-30	40-30	DN 125	DN100	545
3NKV A.D. 15/4 T	60120111	3 X 400 V ~	4	5,5	8-30	50-40	DN 125	DN100	575
3NKV A.D. 15/5 T	60120112	3 X 400 V ~	4	5,5	8-30	65-50	DN 125	DN100	578
3NKV A.D. 15/6 T	60120113	3 X 400 V ~	5,5	7,5	8-30	80-60	DN 125	DN100	662
3NKV A.D. 15/7 T	60120114	3 X 400 V ~	5,5	7,5	8-30	90-70	DN 125	DN100	668

