


Testomat 2000® self clean

LENNTECH

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289



Testomat 2000® self clean is a special version of **Testomat 2000®** with an additional dosing pump for cleaning or disinfecting agents after an analysis. It can be used to remove possible pollution of the measuring chamber and the drain hose. After a preset number of analysis cycles, the measuring chamber is rinsed and the agent is added to the water in the measuring chamber. After a reaction time of 30 seconds, the content of the measuring chamber is dumped. The measuring chamber is subsequently rinsed twice.

Application

- use for difficult water, e.g. calcium, biofims, various other deposits
- extending service life
- reducing contamination in the measuring chamber

Measuring range

0.05-25 °dH Water hardness

0.5-20 °dH Carbonate hardness

1-15 mmol/l p-value

0.05-0.5 mmol/l minus m-value

(depending on the choice of the indicator)

Technical Data

Power supply: 230-240 VAC, 115 VAC, 24 VAC all 50-60Hz

Power consumption: max. 30 VA

Protection class: I

Degree of protection: IP 65

Ambient temperature: 10-45 °C, 50 - 104°F

Option: booster pump see accessories

Dimensions (B x H x T): 380 x 480 x 280 mm

Weight: approx. 9.5 kg

Menu languages: German, English (others upon request)

Mains water supply

Operating pressure:

1 to 8 bar (15 to 116 psi) or

0,3 to 1 bar (5 to 15 psi), after removing of the valve body out of the regulator/filter housing

Water inlet: Opaque hose with 6 mm external diameter/4 mm internal diameter

Water outlet: Hose with 6 mm external diameter/4 mm internal diameter

Water temperature: 10 to 40 °C; 50 to 104°F