

Accessories Testomat® 2000 / 808

T2000 service case



Is used	for Testomat and Titromat devices		
Order number	270337		
Description	Service case for regular maintenance of a Testomat 2000® device		
Technical data	○ 10 20x2 O-rings ○ 10 10.82x1.78 O-rings ○ 5 4.47x1.78 O-rings ○ 5 18x2 EPDM O-rings ○ 20 24x2 flat gaskets ○ 5 x filter screen for inlet, 19.5dx25 ○ 5 flow regulator cores ○ 2 springs for inlet ○ 10 stoppers for measuring chamber ○ 6 fuses, T 0.08A ○ 6 fuses, T 0.1 A ○ 6 fuses, T0.16 A ○ 6 fuses, T 0.2 A ○ 6 fuses, T 0.315 A ○ 6 fuses, T 1.0 A ○ 6 fuses, M4A ○ 20 30x3 sight glasses ○ 3 screw caps with ○ T2000 insert ○ 4 M3x40 screws ○ 1 suction hose ○ 1 pressure hose ○ 6 different pipes ○ 1 cleaning brush set ○ 2 push-in ○ angle joints ○ 2 magnetic stirring bars		


Repair and service case



New

Is used	for Testomat® 808	for Testomat® 808 SiO2
Order number	270342	270343
Description	Case for regular maintenance of a Testomat® 808 / 808 SiO2 and on-site service	
Technical data	○ 8 3.68x1.78 O-rings ○ 8 1.78x1.78 O-rings ○ 8 4.5x1.5 O-rings ○ 8 24x2 flat gaskets ○ 1 pump head ○ 4 500ml inserts with screw cap ○ 1 100ml insert with screw cap ○ 1 cleaning brush set ○ 4 angle screw connectors ○ 6 fuses, T 0.1 A ○ 6 fuses, T 0.2 A ○ 6 fuses, T 1.0 A ○ 6 fuses, T4A ○ 6 30x3 sight glasses ○ 2 pipes, l = 53 mm ○ 2 pipes, l = 140 mm ○ 1 optical board ○ 1 SUB-D null modem cable ○ 1 USB serial adapter ○ 2 dosing needles ○ 4 hose adapters ○ 2 magnetic stirring bars ○ 8 M3x12 screws ○ 4 M3x40 screws ○ 1 LED socket ○ 1 magnetic valve ○ documentation/software (1)	
	Testomat® 808 SiO2 differing: ○ 1 double pump head ○ 6 fuses T0.315A ○ 8 fuses T4A ○ 2 100ml insert with screw cap	

Accessories Testomat® 2000 / 808	Service set	1-Year service set	Service set Testomat PO4
			
Is used	for Testomat 2000®/Testomat ECO®, EVO TH and Titromat®	for Testomat 2000®/Testomat ECO®, EVO TH and Titromat®	for Testomat PO4
Order number	270352	270360	270354
Description	spare part kit for maintenance	small spare part kit for maintenance	spare part kit for maintenance of PO4 device and PeriClip pump
Technical data	○ 1 T2000 gasket kit ○ 2 30x3 sight glass ○ 1 flow regulator cores ○ 3 stoppers for measuring chamber ○ 1 valve kit for injection pump ○ 1 filter screen for intake 19.5 d x 25 ○ 3 different pipes ○ 1 cleaning brush set	○ 1 T2000 gasket kit ○ 2 30x3 sight glass ○ 1 flow regulator cores ○ 3 stoppers for measuring chamber ○ 1 valve kit for injection pump ○ 1 filter screen for intake 19.5 d x 25	○ 1 T2000 gasket kit ○ 2 30x3 sight glass ○ 1 flow regulator cores ○ 3 stoppers for m. chamber ○ 2 x pump head ○ 1 filter screen for intake ○ 3 different pipes ○ 1 cleaning brush set ○ 2 x tube connection ○ 2 x seal for tube connection ○ 2 x screw cap with insert

	PMMA sight glasses	Service set	Service set Testomat Polymer
			
Is used	for Testomat® 808	for Testomat® 808	for Testomat 2000®Polymer
Order number	37653	270351	270353
Description	PMMA sight glasses	Set for regular maintenance	spare part kit for maintenance of Polymer device and PeriClip pump
Technical data	PMMA sight glasses are used when the silicate content in the measuring water exceeds 15 mg/l and prevent silicates clogging up the sight glasses. The kit consists of: ○ 2 24x2 flat gaskets ○ 2 sight glasses	○ 15 24x2 flat gaskets ○ 6 sight glasses ○ 6 3.68x1.78 O-rings ○ 6 4.5x1.5 O-rings ○ 6 1.78x1.78 O-rings ○ 1 pipe, l = 53 mm / 2" ○ 1 pipe, l = 140 mm / 5.5" ○ 1 cleaning brush set	○ 1 T2000 gasket kit ○ 2 30x3 sight glass ○ 1 flow regulator cores ○ 3 stoppers for m. chamber ○ 2 x pump head ○ 1 filter screen for intake ○ 3 different pipes ○ 1 cleaning brush set ○ 2 x tube connection ○ 2 x seal for tube connection ○ 2 x screw cap with insert

LENNTECH

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289