



# PRODUCT SPECIFICATION


## 2.5" ACM-LP RO Element Series

| Model         | Permeate flow<br>GPD (m3/day)* | Average Salt<br>Rejection (%) | Minimum Salt<br>Rejection (%) |
|---------------|--------------------------------|-------------------------------|-------------------------------|
| 2540-ACM4-TSF | 1,000 (3.0)                    | 99.00                         | 98.00                         |

Performance is based on the following test conditions: 2,000.0 ppm NaCl, 225.0 psi, 25°C, 15% recovery, pH 8.0, 30 minutes operation.

### OPERATIONAL AND DESIGN DATA

|                                            |                                                          |
|--------------------------------------------|----------------------------------------------------------|
| Membrane Type.....                         | ACM Fully Aromatic Polyamide Advanced Composite Membrane |
| Configuration.....                         | Spiral Wound, Fiberglass Outer Wrap                      |
| Active Membrane Area.....                  | 26 ft <sup>2</sup> (2.4 m <sup>2</sup> )                 |
| Recommended Applied Pressure.....          | 100 - 300 psi (7 - 21 bar)                               |
| Maximum Applied Pressure.....              | 600 psi (41 bar)                                         |
| Recommended Operating Temperature.....     | 35 - 113°F (2 - 45°C)                                    |
| Feedwater pH Range.....                    | 2 - 11 continuous                                        |
| Chlorine Tolerance.....                    | <0.1 ppm                                                 |
| Maximum Feed Flow.....                     | 6 GPM (1.4 m3/hr)                                        |
| Minimum Brine Flow/Permeate Flow Ratio.... | 5:1                                                      |
| Maximum SDI ( 15 minutes) .....            | 5.0                                                      |
| Maximum Turbidity.....                     | 1 NTU                                                    |



Element Weight : 7 (3.2)  
Length (A) : 40.0 (1,016) Diameter (B) : 2.5 (63) Permeate Tube (C) : 0.75 (19.1)  
Units in pounds and inches, units in paranthesis in kilograms and millimetres.  
Mechanical Configuration: Filmtec Style Core Tube  
Feed Spacer: 0.031" thick diamond spacer

\* Permeate flow is clean water flux at standard conditions above. Not applicable for all feedwater conditions. Individual element's permeate flow may vary +/- 15%.



**Engineered Membrane**  
**SOLUTIONS**



**LENNTECH**

info@lennotech.com Tel.+31-152-610-900  
www.lennotech.com Fax.+31-152-616-289