




Low Fouling RO TurboClean® Element For Dialysis and High-Purity Applications

* Performance is based on the following test conditions: 2,000 ppm NaCl, 225 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 15%.

Membrane Type	X-20™ Polyamide-Urea Advanced Composite Membrane
Configuration	Spiral Wound, Sanitary Style Element
Active Membrane Area	80 ft ² (7.4 m ²)
Typical Applied Pressure	150 - 300 psi (10 - 21 bar)
Maximum Applied Pressure	600 psi (41 bar)
Maximum Operating Temperature.....	113°F (45°C)
Feed pH Range	2 - 11 continuous
Chlorine Tolerance	<0.1 ppm
Maximum Feed Flow	20 GPM (4.5 m ³ /hr)
Maximum Pressure Drop	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Maximum Feed SDI (15 minutes).....	5.0
Maximum Feed Turbidity	1 NTU
Application	High Purity Water
Part Number	194030442
Replaces Model(s)	4040-N1P3U5



Engineered Membrane SOLUTIONS

LENNTECH

info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289