



PRODUCT SPECIFICATION

8" Continuous High Temperature UF Element

Model	Permeate Flow GPD (m3/day)*	Nominal M.W.C.O.
TurboClean® High Temp UA60-8040	6,000 (22.7)	3,500

* Performance is based on the following test conditions: 2,000 ppm MgSO₄, 110 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 15%.

OPERATIONAL AND DESIGN DATA

Membrane Type	UA60 Polypiperazine Amide Ultrafiltration Membrane
Configuration	Continuous High Temperature, Sanitary Style Element
Active Membrane Area	235 ft ² (21.8 m ²)
Typical Applied Pressure	50 - 300 psi (3 - 21 bar)
Maximum Applied Pressure	400 psi (27.6 bar) @ 158°F (70°C)
Maximum Operating Temperature	176°F (80°C)
Feed pH Range	3 - 10 continuous
Chlorine Tolerance	<0.1 ppm
Maximum Feed Flow	80 GPM (18 m ³ /hr)
Maximum Pressure Drop @ 50°C	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Maximum Pressure Drop @ 70°C	5 psi (0.3 bar) per element; 20 psi (1.4 bar) across housing



Element Weight:	45 lbs. (20 kg)		
Length (A):	40.00" (1,016 mm)	Diameter (B):	7.9" (200 mm)
Permeate Tube:		Permeate Tube (C):	1.125" (28.6 mm)
	FilmTec Style polysulfone tube		



**Engineered Membrane
SOLUTIONS**

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289