



The Specialty Membrane Company


PRODUCT SPECIFICATION

8" UF TurboClean® Sanitary Element

Model	Nominal M.W.C.O.
TurboClean® UF 8038-UF10-31	10,000

OPERATIONAL AND DESIGN DATA

Membrane Type	UF10 Advanced Ultrafiltration Membrane
Configuration	Spiral Wound, Sanitary Element
Active Membrane Area	355 ft ² (32.6 m ²)
Typical Applied Pressure	30 - 150 psi (2 - 10 bar)
Maximum Applied Pressure	300 psi (20 bar)
Maximum Operating Temperature	122°F (50°C)
Feed pH Range	2 - 11 continuous
Chlorine Tolerance	180 ppm for sanitization @ pH ≥ 10.5
Maximum Feed Flow	80 GPM (18 m ³ /hr)
Maximum Pressure Drop	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Replaces Model	TurboClean® UF 8038-UE10-31, 8038-N6D9V8



Element Weight:	36 lbs. (16 kg)		
Length (A):	38.0" (965 mm)	Diameter (B): 7.9" (200 mm)	Permeate Tube (C): 1.125" (28.6 mm)
Permeate Tube:	Polysulfone tube; Interconnect and ATDs not included with element		
Feed Spacer:	0.031" thick diamond spacer		



Engineered Membrane
SOLUTIONS

LENNTECH

info@lenntech.com Tel. +31-152-610-900
www.lenntech.com Fax. +31-152-616-289