

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289


Zeta Plus™ HT Series

Lenticular Depth Filter Cartridges

Zeta Plus HT Series is a charge-modified depth filter constructed with high-tensile strength media to perform efficiently even under operating conditions requiring elevated operating temperatures or repeated hot water sanitation cycles. Zeta Plus HT filter media is made from inorganic filter aids, refined cellulose and cationic resin.

Grade Selection

The Zeta Plus HT series filter media are available in several grades, that meet the different filtration needs required by your applications. Nominal filtration ratings are given in the following table for the various grades. The optimal filtration system for your particular application can be determined by on-site testing or by sample evaluation by a member of our Scientific Application Support Services group (SASS).



Graphic 1: Zeta Plus HT Grade Selection



Picture 1: Zeta Plus Family

Applications

Beverage, spirits

Food Products

Fine Chemicals

Oral products

Cosmetics

Water treatment

Features and Benefits

More than three times the strength of competitive media to withstand multiple steaming and hot water sanitisation cycles

- Extended filter life resulting in high throughputs, fewer cartridge change-outs and reduced operating costs

Combined depth filtration and electro-kinetic adsorption

- Efficient haze and particle removal at micron ratings smaller than the mechanical rating alone

Easy-to-install cartridges for rapid change-out

- Reduced labour cost

Totally enclosed, sanitary systems and housings

- Zero edge leakage and external contamination

Variety of cartridge sizes and filtration surface areas

- Flexible options for all flow requirements

All components FDA CFR Title 21 listed

- Safe for all food & beverage filter applications

3M




Figure 1: Zeta Plus Cartridge Construction

Cartridge Construction

Zeta Plus HT cartridges are constructed from individual cells. Each cell is constructed using polypropylene moulded edge seals and internal separators for high performance. The cells are made into a single unit by three 316 stainless steel bands in the core of the cartridge with polypropylene cell separators. Various gasket materials are available depending upon application. Filter cartridges are available in 8, 12 and 16-inch diameters.


Zeta Plus Cartridge System Vs. Plate & Frame Filter Economics

The Zeta Plus cartridge system has a number of advantages over conventional plate and frame filters. Since the cartridge system utilises a totally enclosed housing, there is no product leakage and no exposure of the filter media to external contamination allowing for effective use of the media, higher throughputs and low operating costs. The plate and frame filter press design is open to the environment making both filter media and product susceptible to external contamination. The “open” design requires more frequent media change-out cycles, typically every few days. This results in lower throughputs and higher operating costs.

Plate and frame filters are labour intensive, requiring two people four to eight hours to change out the media. Zeta Plus cartridges are easy to install and remove, usually taking about 15 minutes, resulting in significant labour cost reductions. Coupled with the floor space reduction of the vertical Zeta Plus housing design and a typical 50% or greater decrease in initial capital cost when compared to a comparable plate and frame filter, the savings become substantial.

Flow Rates Characteristics

The graph shows initial Δp values for Zeta Plus HT series filter media versus specific flow rates (l/min/m²), obtained with clean water.



Graphic 2: Zeta Plus HT Flow Rate Graph

Quality Control

The Zeta Plus HT cartridges are manufactured following an ISO quality certified assurance scheme. All the cartridges are labelled with a lot identification number to provide complete traceability. Moreover, each cartridge is graved with its lot number and grade assuring total traceability.

Compatibility

The gaskets compatibility with different chemicals is indicated in table 1. It is advisable to test a product under service conditions simulating service conditions. *These recommendations are intended as a guide only.*

CHEMICALS	HT	GASKETS			
		Nitrile	Fluorocarbon	Ethylene Propylene	Silicone
Acetic Acid 5%-20%	G	G	G	G	G
Acetone 100%	G	P	G	G	G
Benzene	G	P	F	P	F
Carbon Tetrachloride	G	F	G	P	F
Chloroethylene	G	P	G	P	F
Chloroform - Dry	G	P	G	P	F
1,4 - Dioxane	G	P	P	P	P
Ethanol 10% and 50%	G	G	F	G	G
Ethyl Acetate	G	P	P	P	F
n-Heptane	G	G	G	P	F
Hexane	G	G	G	P	F
1,1,1 - Trichloroethane	G	P	G	P	F
Methanol	G	G	P	G	G
Methyl Ethyl Ketone (MEK)	G	P	P	G	G
Methyl Isobutyl Ketone (MIBK)	G	P	P	G	G
Sodium Hydroxide 20%	F-P	F	G	G	G
Toluene	G	P	G	P	F
Water (25 °C and 82 °C)	G	G	G	G	G

Explanation of ratings:
 G = Satisfactory - to maximum 82°C (unless restriction is noted).
 F = Fair
 P = Not recommended.

Table 2: Zeta Plus HT series extractables

		GRADE				
		8 HT	015 HT	050 HT	080 HT	150 HT
Deminer-alised water	Calcium (ppm)	0.18	0.09	0.12	0.13	0.15
	Iron (ppb)	<5.0	<5.0	<5.0	<5.0	5.27
Ethanol 8%	Calcium (ppm)	0.26	0.09	<0.08	<0.08	0.09
	Iron (ppb)	<5.0	<5.0	<5.0	<5.0	<5.0
Ethanol 50%	Calcium (ppm)	0.10	<0.08	<0.08	<0.08	<0.08
	Iron (ppb)	<5.0	<5.0	<5.0	<5.0	<5.0

Table 3: Microorganism Retention

Zeta Plus HT	Microorganisms used for challenge	Retention efficiency (%)
015 HT	Saccharomyces cerevisiae (ATCC - 36026)	> 99.99
050 HT		> 99.99
080 HT		> 99.99
080 HT	Oenococcus oeni (ATCC - 23279)	> 99.99
150 HT		> 99.99
080 HT	Brevundimonas diminuta (ATCC - 19146)	> 99.99
150 HT		> 99.99

Extractables

Table 2 gives as an example values for calcium and iron in 3 different extracting solutions due to soak testing. Moreover, specific rinsing procedures can be developed on-site for special applications.

Microorganisms Retention

Test conditions: specific flow rate: 635 l/h/m², initial micro-organism concentration: 108 organisms/cm² of media. The results in table 3 show the retention efficiency of Zeta Plus HT series filter.

Operating Parameters

	Maximum Operating Pressure	Maximum Operating Temperature	Recommended Flush	Sterilisation Parameters	Maximum Flow Rate (FLUX) (in l/min per m ²)
Standard and Special pre-coat Zeta Plus Cartridges	2.4 bar	82 °C	54 l/m ² at 20 lpm/m ²	autoclave or in-situ steam sterilisation for 1 hour at 121 °C	1.2 to 12

Zeta Plus HT Series Ordering Guide

1. Cartridges

Zeta Plus	Diameter (inch)	Cartridge Design	Gasket Type	Grade	Formulation
Z	08	P = Plug-in 7 cells (0.23 m²)	Standard A = Silicone (MVQ)*	003 8 015 050 080 150	HT
		D = Standard 8 cells (0.26 m²)	Standard D = Nitrile (NBR)*		
	12	C = 9 cells / small (0.85 m²) B = Special pre-coat 12 cells (1.1 m²) D = Standard 16 cells (1.5 m²) S = Special 7 cells (0.7 m²)	Options A = Silicone (MVQ)* B = Fluorocarbon (FPM)* C = EPR (EPDM)*		
	16	M = Standard diffusion netting 14 cells (3.2 m²) D = Standard 15 cells (3.4 m²) S = Special precoat 9 cells (2.1 m²)	*ISO Designation		

Important Notice

3M Purification MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Since a variety of factors can affect the use and performance of a 3M Purification product in a particular application, some of which are uniquely within the user's knowledge and control, user is responsible for determining whether or not the 3M Purification product is fit for a particular purpose and suitable for user's method of application.

Limited Warranty

3M Purification warrants this product to be free from defects in material and workmanship during normal use for a period of one (1) year from the date of shipment from the factory. If the Product(s) is (are) defective within this warranty period, your exclusive remedy and 3M Purification's sole obligations shall be, at 3M Purification's option, to replace or repair the Product(s) or refund the original purchase price of the Product(s). This warranty does not apply to failures that result from abuse, misuse, alteration or damage not caused by 3M Purification or failure to properly follow installation and use instructions.

Limitation of Liability: 3M Purification will not be liable for any loss or damage arising from the use of the Product(s), whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.

This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.

Zeta Plus and 3M are trademarks of 3M used under license.

LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289



Data may be subject to change without further notice.

© 3M 2010. All rights reserved.

v.2 - DOC10026
LITCTZPHT1.EU - 1110

Z 08 P A 003 HT	Z 16 S A 015 HT	Z 12 C C 050 HT
Z 08 P A 8 HT	Z 16 S A 050 HT	Z 12 C C 080 HT
Z 08 P A 015 HT	Z 16 S A 080 HT	Z 12 C C 150 HT
Z 08 P A 050 HT	Z 16 S A 150 HT	Z 12 C D 003 HT
Z 08 P A 080 HT	Z 16 S B 003 HT	Z 12 C D 8 HT
Z 08 P A 150 HT	Z 16 S B 8 HT	Z 12 C D 015 HT
Z 08 D A 003 HT	Z 16 S B 015 HT	Z 12 C D 050 HT
Z 08 D A 8 HT	Z 16 S B 050 HT	Z 12 C D 080 HT
Z 08 D A 015 HT	Z 16 S B 080 HT	Z 12 C D 150 HT
Z 08 D A 050 HT	Z 16 S B 150 HT	Z 12 B A 8 HT
Z 08 D A 080 HT	Z 16 S C 003 HT	Z 12 B A 015 HT
Z 08 D A 150 HT	Z 16 S C 8 HT	Z 12 B A 050 HT
Z 08 D B 003 HT	Z 16 S C 015 HT	Z 12 B A 080 HT
Z 08 D B 8 HT	Z 16 S C 050 HT	Z 12 B A 150 HT
Z 08 D B 015 HT	Z 16 S C 080 HT	Z 12 B B 003 HT
Z 08 D B 050 HT	Z 16 S C 150 HT	Z 12 B B 8 HT
Z 08 D B 080 HT	Z 16 S D 003 HT	Z 12 B B 015 HT
Z 08 D B 150 HT	Z 16 S D 8 HT	Z 12 B B 050 HT
Z 08 D C 003 HT	Z 16 S D 015 HT	Z 12 B B 080 HT
Z 08 D C 8 HT	Z 16 S D 050 HT	Z 12 B B 150 HT
Z 08 D C 015 HT	Z 16 S D 080 HT	Z 12 B C 003 HT
Z 08 D C 050 HT	Z 16 S D 150 HT	Z 12 B C 8 HT
Z 08 D C 080 HT	Z 16 M A 015 HT	Z 12 B C 015 HT
Z 08 D C 150 HT	Z 16 M A 050 HT	Z 12 B C 050 HT
Z 08 D D 003 HT	Z 16 M A 080 HT	Z 12 B C 080 HT
Z 08 D D 8 HT	Z 16 M A 150 HT	Z 12 B C 150 HT
Z 08 D D 015 HT	Z 16 M B 003 HT	Z 12 B D 003 HT
Z 08 D D 050 HT	Z 16 M B 8 HT	Z 12 B D 8 HT
Z 08 D D 080 HT	Z 16 M B 015 HT	Z 12 B D 015 HT
Z 08 D D 150 HT	Z 16 M B 050 HT	Z 12 B D 050 HT
Z 12 D A 8 HT	Z 16 M B 080 HT	Z 12 B D 080 HT
Z 12 D A 015 HT	Z 16 M B 150 HT	Z 12 B D 150 HT
Z 12 D A 050 HT	Z 16 M C 003 HT	Z 12 S A 8 HT
Z 12 D A 080 HT	Z 16 M C 8 HT	Z 12 S A 015 HT
Z 12 D A 150 HT	Z 16 M C 015 HT	Z 12 S A 050 HT
Z 12 D B 003 HT	Z 16 M C 050 HT	Z 12 S A 080 HT
Z 12 D B 8 HT	Z 16 M C 080 HT	Z 12 S A 150 HT
Z 12 D B 015 HT	Z 16 M C 150 HT	Z 12 S B 003 HT
Z 12 D B 050 HT	Z 16 M D 003 HT	Z 12 S B 8 HT
Z 12 D B 080 HT	Z 16 M D 8 HT	Z 12 S B 015 HT
Z 12 D B 150 HT	Z 16 M D 015 HT	Z 12 S B 050 HT
Z 12 D C 003 HT	Z 16 M D 050 HT	Z 12 S B 080 HT
Z 12 D C 8 HT	Z 16 M D 080 HT	Z 12 S B 150 HT
Z 12 D C 015 HT	Z 16 M D 150 HT	Z 12 S C 003 HT
Z 12 D C 050 HT	Z 16 D A 015 HT	Z 12 S C 8 HT
Z 12 D C 080 HT	Z 16 D A 050 HT	Z 12 S C 015 HT
Z 12 D C 150 HT	Z 16 D A 080 HT	Z 12 S C 050 HT
Z 12 D D 003 HT	Z 16 D A 150 HT	Z 12 S C 080 HT
Z 12 D D 8 HT	Z 16 D B 003 HT	Z 12 S C 150 HT
Z 12 D D 015 HT	Z 16 D B 8 HT	Z 12 S D 003 HT
Z 12 D D 050 HT	Z 16 D B 015 HT	Z 12 S D 8 HT
Z 12 D D 080 HT	Z 16 D B 050 HT	Z 12 S D 015 HT
Z 12 D D 150 HT	Z 16 D B 080 HT	Z 12 S D 050 HT
Z 12 C A 8 HT	Z 16 D B 150 HT	Z 12 S D 080 HT
Z 12 C A 015 HT	Z 16 D C 003 HT	Z 12 S D 150 HT
Z 12 C A 050 HT	Z 16 D C 8 HT	
Z 12 C A 080 HT	Z 16 D C 015 HT	
Z 12 C A 150 HT	Z 16 D C 050 HT	
Z 12 C B 003 HT	Z 16 D C 080 HT	
Z 12 C B 8 HT	Z 16 D C 150 HT	
Z 12 C B 015 HT	Z 16 D D 003 HT	
Z 12 C B 050 HT	Z 16 D D 8 HT	
Z 12 C B 080 HT	Z 16 D D 015 HT	
Z 12 C B 150 HT	Z 16 D D 050 HT	
Z 12 C C 003 HT	Z 16 D D 080 HT	
Z 12 C C 8 HT	Z 16 D D 150 HT	